Ti-sa-				Water Well Reco	ord Form WWC-		- 		
LOCATION OF WATER WELL:			FRACTION			Section Number	Township Number	Range Number	
Sedgwick			SW 1/4		SE 1/4	8	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?									
1437 N. Rochester Wichita, Kansas									
WA	TER WELL (OWNER: NORTH	H HIGH SCH	IOOL US	50 259				
RR#,	ST. ADRESS,		N. Roches	ster			Board of Agriculture, D	livivsion of Water Resource	
CITY	, STATE, ZIP	code: Wichi	ita, Kansa	1S			Application Numbe	er:	
		LOCATION WITH 4		MPLETED WELL	45	ft. ELE	VATION:		
AN "X'	' IN SECTION	N BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
i †			WELL'S STATIC W	ATER LEVEL 2	20 F7	Г. BELOW LAND SUR	RFACE MEASURED ON mo/day/yr	03/12/1997	
	NW	NE	Pump tes	Pump test data: Well water was			after hours pum		
			est. Yield	gpm: Well	l water was		after hours pum	- 	
W M		EB	ore Hole Diameter	12 in.	to 45	ft.	and in.	to ft.	
= "			VELL WATER TO I	-	5 Public water			njection well	
١.			1 Domestic	3 Feedlot	6 Oil field w			Other (Specify below)	
	SW		2 Irrigation	4 Industrial	7 Lawn and	garden only 1	0 Monitoring well		
↓		<u> X</u> w	Was a chemical/bacte	eriological sample :	submitted to D	epartment? Yes	No X; If yes, m	no/day/yr sample was	
		2	submitted			-		X No	
5 TY	PE OF CA	SING USED:		5 Wrought iron	1 /	8 Concrete tile		Glued X Clamped	
1 Stee	i	3 RMP (SR)		6 Asbestos-Cem	_	9 Other (Specify be		Velded	
2 PVC	2	4 ABS		7 Fiberglass		SDR-26	•	[hreaded	
Blank casing Diameter 6 in. to 25 ft., Dia in. to ft., Dia in. to ft.									
		ve land surface 12		weight			Wall thickness or gauge No.	.255	
		EN OR PERFORATION		ū		7 PVC	10 Asbestos-ceme		
1 Stee	:l	3 Stainless Steel		5 Fiberglass	,	8 RMP (SR)	11 other (specify	ÿ)	
2 Bras	is	4 Galvanized steel		6 Concrete tile	•	9 ABS	12 None used (op	pen hole)	
SCREE	N OR PEI	RFORATION OPEN	ING ARE:	5 Ga	uzed wrapped		8 Saw cut	11 None (open hole)	
	nous slot	3 Mill slot			re wrapped		9 Drilled holes		
2 Louve	red shutte	r 4 Key pund	ched	7 Tor	ch cut		10 Other (specify)		
SCREE	N-PERFO	RATION INTERVAL	LS: from 25		ft. to 45	ft., From	ft. to	ft.	
			from		ft. to	ft., From		ft.	
GRAVEL PACK INTERVALS: from 24									
GRAVEL FACE INTERVALS: ITOM 24					ft. to	ft., From ft., From		ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
	tervals:		ft. to 24	ft. From			. 54.0.	& 4a &	
		t source of possible co		ft. From ft.		to 10 Livestoc	ft. From ck pens 14 A	ft. to ft. Abandon water well	
1 Septi		4 Lateral l				11 Fuel sto		15 Oil well/Gas well	
2 Sewe		5 Cess po		8 Sewage lagoon		12 Fertiliza	13(16 Other (specify below)	
	rtight sewe	-					ida stances	Apparent	
	n from wel		e pir	/ 1 company			How many feet?	, whharenc	
FROM	TO		THOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
0	3	topsoil			<u> </u>	1 1	The state of the s	W 1.1 Law	
3	17	clay	•			1 1			
17	23	fine sand	1						
	45	medium sa							
			144						
								and the second s	
						1 1			
						<u> </u>			
						1 1			
7 COMPACTIONS									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Was co	mpietea	on (mo/day/year)		#X.X./	and this re	cord is true to the	e best of my knowledge and	belief. Kansas water A / Q 7	
I Inder	Ontractor	''s License nof	www	This water went	Record was d	completed on the	o/day/yr)	*./	
Ulluci	lic Dusin	ICSS HAHR VI.MMM	· #	A. MINE 185. 187. 187. 187. 187. 187. 187. 187. 187	in de la	MM by (signe	Iodd L	Hann	