1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	T	Range Number
		CB C	7.7		Township Number	1
Sedgwick	SE 1/4		W 1/4	27	T 27 s	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?						
2245 Aloma	Wichita,	Kansas				
WATER WELL OWNER: MURRAY, Jim  RRW, ST. ADRESS, BOX #: 2245 Along  Board of Agriculture, Divivsion of Water Resource						
ZZ45 ATOMA						NIVSION OF WATER RESOURCE
				Application Number:		
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		WELL	. 30		EVATION:	
N. N. SECTION BOX.	Depth(s) groundwa		1	ft.	2 ft.	3 n.
	WELL'S STATIC W		5.5 FT.	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	08/11/1997
NWNE	Pump test	data: Well w	vater was	ft.	after hours pum	ping gpm
	Est. Yield		vater was	ſt.	after hours pum	ping gpm
	Bore Hole Diameter U	<u>~</u>	to	ſt.	and in.	to ft.
WELL WATER LOSED AS: 5 Public water supply 8 Air conditioning 11 Injection well						-
sw						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was						
S submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped						
1 Steel 3 RMP (SR)	6 Asbestos-Cemen	ıt 9	Other (Specify b			
2 PVC 4 ABS		7 Fiberglass			T	hreaded
Blank casing Diameter 5	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height see thand surface 3		weight		lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) N/A						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPE	NING ARE:	5 Gauze	ed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slo	ot :		wrapped		9 Drilled holes	
2 Louvered shutter 4 Key pu	mched	7 Torch	cut		10 Other (specify) N/	/ n
SCHEEN BEDECH ATION INTERNALS					ft.	
		ft. to		ft., Fron		
from GRAVEL PACK INTERVALS: from		ft. to ft. to		ft., Fron ft., Fron		ft.
from		ft. to		ft., From		n. n.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
Grout Intervals: From 2 ft. to 8 ft. From ft. to ft. From 8 ft. to 16 ft.						
What is the nearest source of possible contamination:				10 Livesto		bandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel st		oll well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertili		Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent						
Direction from well?						
	LITHOLOGIC LOG		FROM	ТО	PLUGGING INTER	RVALS
			0		surface silt an	
			2		cement grout	The second secon
			8		bentonite hole	plug
			16		chlorinated san	
	***************************************			1		
			<u> </u>			
					Mark the second	
				-		
			<b>-</b>			
				<u> </u>		
7 CONTRACTOR'S OR LANDOWNER	R'S CERTIFICATION: Thi	s water well was (1	l) constructe	ed, (2) reconstr	ucted, or (3) plugged under m	ny jurisdiction and
was completed on (mo/day/year)	08/11/	1997	and this rec	ord is true to t	he best of my knowledge and	belief. Kansas Water
Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr)						
Under the business name of HarpNell						
Todd S. Harp						