

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction NW 1/4 NW 1/4 NE 1/4	Section Number 18	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 100' WEST OF 13th & PERRY WICHITA KS MW 7					
2 WATER WELL OWNER: KDHE RR#, St. Address, Box #: FORBES FIELD City, State, ZIP Code: TOPEKA KS Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 22 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 22 ft. below land surface measured on mo/day/yr 9/23/97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 27 ft. and in. to ft.			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded X
Blank casing diameter 2 in. to 47 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 0 in., weight lbs./ft. Wall thickness or gauge No. SCH 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	11 Other (specify)
					12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 17 ft. to 27 ft., From ft. to ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 15 ft. to 27 ft., From ft. to ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 0 ft. to 13 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? How many feet? 200'					
FROM TO LITHOLOGIC LOG			FROM TO PLUGGING INTERVALS		
0 14 SILTY LEAN TO FAT CLAY					
14 17 SANDY FAT CLAY					
17 27 FINE TO COARSE SAND W/ GRAVEL					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, 2 reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9-23-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 10-17-97 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)					