1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	1 Form WWC-5	KSA 82a-1212 Section Number	T = 1131	T = 5, ;	
		-			Township Number	Range Number	
Sedgwick	SW 1/4		SE 1/4	9	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
13th and Ohio Wichita, Kansas							
WATER WELL OWNER: WICHI	TA, CITY						
RR#, ST. ADRESS, BOX#: 455 N. Main Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Wichita, Kansas				- · · · · · · · · · · · · · · · · · · ·			
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WEL			4.0				
AN "X" IN SECTION BOX:			40		VATION:	_	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	ELL'S STATIC W	ATER LEVEL 1:	3 гт.	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	02/17/1999	
NWNE	Pump tes	t data: Well v	water was	ft. a	fter hours pum	ping gpm	
I F.s	t. Yield	gpm: Well	water was	ft. a	fter hours pum		
E Bo	re Hole Diameter	12 in.	to 40	ft.	and in.	to ft.	
E BO	ELL WATER TO		5 Public wate			njection well	
]	1 Domestic				U	•	
swse			6 Oil field wa		•	ther (Specify below)	
1 I Manufacture were							
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was							
S	ubmitted			Wate	r Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cemer		Other (Specify bel		elded	
2 PVC 4 ABS		7 Fiberglass		`	,	hreaded	
	4 00	-		DR-26		in caucu	
Blank casing Diameter 8 in	to 20	ft., Dia	in.		ft., Dia in.	to ft.	
Casing height above land surface 12	in.,	weight 5			Vall thickness or gauge No.	.332	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)							
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (op	en hole)	
SCREEN OR PERFORATION OPENI	NG ARE:	5 Gauz	ed wrapped		8 Saw cut	11 None (open hoie)	
1 Continous slot 3 Mill slot			6 Wire wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punc	hed		==				
/ Torch cut							
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to					ft.		
from		ft.	to	ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 20		ft. to 40		ft., From	ft. to	ft.	
	from	<u> </u>	to	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
	. to 20	ft. From				~	
What is the nearest source of possible contamination:				to 10 Livestocl	ft. From	ft. to ft.	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel stor		14 Abandon water well	
2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		• •			- 130	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fertilize		ther (specify below)	
3 Watertight sewer lines 6 Seepage	9 Feedyard	13 Insecticide st		de storage None	Apparent		
Direction from well?			How many feet?				
	HOLOGIC LOG		FROM	TO	PLUGGING INTER	VALS	
0 3 topsoil							
3 12 clay			İ				
12 17 fine sand							
17 17.5 clay							
17.5 25 medium to	702×70 7	and		 			
illedidii to	COALDE B	and					
				- 			
			_	-			
							
				-			
			1	 			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No2	36	This Water Well R	ecord was co	ompleted on (mo	(day/yr) 02/18	3/99	
Under the business name of Har	Well &	Pump Servi	ice. In	C hv /signal	ture)		
					Todd S	. Haro	