I ocation or water transmit	EDACTION	Water Well Record	Form WWC-5	KSA 82n-1212			
LOCATION OF WATER WELL:	FRACTION		[Section Number	Township Number	Range Number	
Sedgwick Distance and direction from nearest town or city s	NW 1/4	NE 1/4 S	E 1/4	18	T 27 s	R 1E E/W	
•		•					
956 Perry WATER WELL OWNER: SHIDE	Wichita, ELER, Char						
RR#, ST. ADRESS, BOX#: 956	•	res			Board of Agriculture, D	ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wich:	g	- · · · · · · · · · · · · · · · · · · ·					
LOCATE WELL'S LOCATION WITH 4	DEPTH OF POM		27	ft. EI	EVATION:	1.	
AN "X" IN SECTION BOX:	Depth(s) groundwa	UU '	1	ft.	2 ft.	3 ft.	
	VELL'S STATIC WA		FT.	BELOW LAND S	URFACE MEASURED ON mo/day/yr	02/22/1999	
NWNE	Pump test	data: Well wa	iter was	ſt.	after hours pum		
l III	st. Yield	gpm: Well wa	ater was	ft.	after hours pum	**	
E B	ore Hole Diameter	nknown in. t	0	ft.	and in.	to ft.	
	/ELL WATER T O B	EUSED AS: 5	Public water	supply	8 Air conditioning 11 I	njection well	
swse	1 Domestic		Oil field wat		9 Dewatering 12 C	Other (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and ga	ırden only	10 Monitoring well		
C		riological sample sub	mitted to De	•		io/day/yr sample was	
	submitted				ater Well Disinfected? Yes	X No	
TYPE OF CASING USED: 1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement		Concrete tile		lued Clamped	
2 PVC 4 ABS		7 Fiberglass	91	Other (Specify	•	Velded Threaded y	
	. 40		1	4		2.	
Blank casing Diameter 1 1/4 in Casing height asset land surface 60		ft., Dia	in.	to lbs. / ft.	ft., Dia in. Wall thickness or gauge No.	to ft.	
TYPE OF SCREEN OR PERFORATION	•	weight		PVC	10 Asbestos-ceme	ent	
1 Steel 3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (specify) N/A	
2 Brass 4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (or		
SCREEN OR PERFORATION OPEN	ING ARE:	5 Gauzeo	l wrapped		8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key pund	7 Torch cut		10 Other (specify) N	/A			
SCREEN-PERFORATION INTERVAL	LS: from	ft. t	0 -	ft., Froi	•	ft.	
	from	ft. t	0	ft., Fro		ft.	
GRAVEL PACK INTERVALS: from		-		ft., Fro		ft.	
from		ft. to ft., F		ft., Fro	m ft. to	n.	
6 GROUT MATERIAL: 1 Neat cer	nent 2 Ce	ement grout	3 Ben	tonite	4 Other bentonite	hole plug	
Grout Intervals: From 0 ft. to 3		ft. From			ft. From 3 ft. to 27 ft.		
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines		7 Die maiere	10 Livestock po		• 170	14 Abandon water wen	
					el storage 15 Oil well/Gas well rtilizer storage 16 Other (specify below)		
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		9 Feedyard	12 1		ecticide etoroge		
Direction from well?	e pit	7 reeuyaru				Apparent	
FROM TO LITHOLOGIC LOG					How many feet? PLUGGING INTER	PLUGGING INTERVALS	
			0	3	cement grout		
			3	27	bentonite hole	plug	
				<u> </u>			
	THE STATE OF THE S						
				ļ			
i i							
7 CONTRACTOR'S ON LANDOWN PRO	GENTLEMAN TON. This			d (2) recent			
7 CONTRACTOR'S OR LANDOWNER'S was completed on (mo/day/year)	CERTIFICATION: This	s water well was (1)	constructe	d, (2) reconst	ructed, or (3) plugged under n	ny jurisdiction and	
was completed on (mo/day/year) Well Contractor's License No	02/22/1 236 1	.999a This Water Well Red	nd this reco	ord is true to t impleted on (r	he best of my knowledge and no/day/yr)	belief. Kansas Water	
7 CONTRACTOR'S OR LANDOWNER'S was completed on (mo/day/year)	02/22/1 236 1	.999a This Water Well Red	nd this reco	ord is true to t impleted on (r	he best of my knowledge and no/day/yr)	belief. Kansas Water	