LICCA	TION OF WA	TED WELL.	Т	FRACTION	Water	Well Reco	ord Form WWC		KSA 82a-1212 Section Number	T	N	P	Number
				NW	1/4	NE 1/4		16	1	Number 7 s	Range	Number Tr	
Distance and direction frem nearest town or city street address of well if located							NE 1/4		10	т 2	7 s	<u> </u>	E E/W
13th N. and Ohio Wichita, Kansas													
WATER WELL OWNER: WICHITA, CITY OF													
RR#,	ST. ADRESS,	BOX#: 455	N M	lain						1	Board of Agriculture, Di		
CITY, STATE, ZIP CODE: Wichita, Kansa										7203 Application Number: 990003			
	TE WELL'S L " IN SECTION	OCATION WITH	_	EPTH OF CO						EVATION:	_		_
1	2.220110.	N	i '	, .	vater Encountered 1 /ATER LEVEL 16			тъ	ft.	2 DEACE MEASUR	ft. ED ON mo/day/yr	3	ft.
		^	WEL	L'S STATIC W Pump tes		_	LO ^r water was	1. В	ft.	after	hours pum	•	/1999
'	NW	NE	Est. Y	•	gpm:		l water was		ft.	after	hours pum	_	gpm gpm
Mile M	,			Iole Diameter	13	in.	to 40		ft.	and	in.	to	ft.
Įξw			WELL	WATER TO		AS:	5 Public was	er s	upply	8 Air conditio	ning 11 I	njection well	
١.	sw	sie	1	Domestic	3 Feedlo		6 Oil field w			9 Dewatering		ther (Specif	y below)
1			2	Irrigation	4 Indust	rial	7 Lawn and	gar	den only	10 Monitoring			
									No X; If yes, m	• •	-		
submitted water wen Dismitted: Yes X No													
1 Stee		3 RMP (SR)			5 Wrou 6 Asbest		-	_	Concrete tile CASING JOINTS: Glued X Clamped Other (Specify below) Welded				
2 PVC 4 ABS									R-26	,	Threaded		
	 asing Diam		in.	to 20	ft.,	Dia	i.		to	ft., Dia	in.	to	ft.
Casing height above land surface 12 in., weight 5.52 lbs./ft. Wall thickness or gauge No332													332
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement													
1 Ste		5 Fibergl				MP (SR)		11 other (specify					
2 Bra		4 Galvanized ste	4.00	o Concre				BS	8 Saw cut	12 None used (open hole)			
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot						5 Gauzed wrapped 6 Wire wrapped			8 Saw cut 11 None (open hole 9 Drilled holes				open noie)
	red shutte		unched				ch cut			10 Other			
		RATION INTER		from 20	1		ft. to 40		ft., Fron		ft. to		ft.
				from	,		ft. to		ft., Fron		ft. to		ft.
GRAVEL PACK INTERVALS: from 20)	ft. to 40			ft., From		ft. to		ft.
<u></u>				from			ft, to		ft., From	n	ft. to		ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug													plug
Grout Intervals: From 0 ft. to 20 What is the nearest source of possible contamination:						ft. From f			to ft. 1				
1 Septic tank 4 Lateral lines					7 Pit privy				11 Fuel storage		14 Abandon water well		
2 Sewer lines 5 Cess pool						8 Sewage lagoon			12 Fertilizer storage		15 Oil well/Gas well 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage plt						9 Feedyard			13 Insect	icide storage	None Apparent		
1	n from wel					•				How mar		ppar	CIIC
FROM	то		LITHO	LOGIC LOG			FROM		TO		LUGGING INTE	RVALS	
0	3	topsoil											
3	11	clay				·····		\dashv					
11 19	19 32	fine same						\dashv		······································			
32	40	grey sha						┪					
	1	groj bi	4 - V			-		\exists					
								_					
	-							_					
<u> </u>													
								\exists					
7 CO	NTRACTO	R'S OR LANDOWN	ER'S CER	TIFICATION: Th	is water w	ell was	s (1) constru	ctec	i, (2) reconst	ructed, or (3)	plugged under n	ny jurisdicti	on and
was c	ompleted	on (mo/day/yea	r)	01/08/	1999		and this r	eco	rd is true to t	he best of my	knowledge and	belief. Kan	ısas Water
Well (Contractor	's License No	23.6	מסוו כ	This Water	er Well	Record was	cor	mpleted on (r	no/day/yr)	01/1	3/.9.9	*********
Under	r tne busir	ess name of.H	M.T.D	.አ/.ም.ተ.ት%	<u>Q</u>	'S'2''	Y	ww	by (sigi	nature)	Todd L	Har	
													N. J.