l con	TION OR III	Tan sant I	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number		T
LOCA	TION OF WA						Township Number	Range Number
Sedgwick NW 1/4					VE 1/4	16	т 27 в	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?								
13th North and Ohio Wichita, Kansas WATER WELLOWNER: WICHITA, CITY OF								
ப			•	OF			Board of Agriculture.	Divivsion of Water Resource
	ST. ADRESS,		N. Main ita, Kansa	_		67203		
$\overline{}$, STATE, ZIP		DEPTH OF COM					et: 330003
	' IN SECTION		Depth(s) groundwa		1	it. Ei	2 ft.	3 ft.
l +	-	- 	WELL'S STATIC W		_		URFACE MEASURED ON mo/day/yr	01/19/1999
			Pump test		water was	ft.	after hours pu	
'	NW	NE	Est. Yield	****	water was	ft.	after hours put	1 0 61
Mile M		1 1 1	Bore Hole Diameter	12 in.	to 40	ft.	and in.	
			WELL WATER TO I		5 Public water			Injection well
			1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)
	sw		2 Irrigation	4 Industrial	7 Lawn and g	•	10 Monitoring weli	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr s							mo/day/yr sample was	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Stee	el .	3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify		Welded
2 PVC		4 ABS		7 Flberglass	S	DR-26		Threaded
Blank ca	 sing Diam	eter 8	in. to 20	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing l	neight abov	e land surface 1	2 in.,	weight 5	5.52	lbs. / ft.	Wall thickness or gauge No.	.332
TYPE (OF SCREE	N OR PERFORAT	ION MATERIAL:			PVC	10 Asbestos-cen	
1 Ste	el	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (speci	fy)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								open hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gau					zed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrap							9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 20 ft. to 40 ft., From ft. to ft.								
			from	ft	. to	ft., Fro	om ft. to	ft.
	GRAVI	EL PACK INTERV	ALS: from 20	ft. to 40		ft., Fro	om ft. to	ft.
<u> </u>		43.	from		. to	ft., Fro		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From ft. to ft. From						to	ft. From 0	ft. to 20 ft.
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines				7 Pit privy	7 Pit privy 11 Fuel storage		1	Abandon water well
				8 Sewage lagoon				Oil well/Gas well
1		5 Cess p			9 Feedvard 13 Insecticide storage		ticide storage	Other (specify below)
White agreement was a seepage pit seeman and the seema								
Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0	3	topsoil					120001101111	24,114,00
3	15	clay						
15	23	fine sand	d					
23	32	medium s						
32	40	grey sha						
						-		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No23.6								
Under the business name of Date								
							O O O O	J. JUULU