l'ani			FRACTION	Water Well R	ecord Form WWC			1
1	TION OF WA					Section Number	Township Number	Range Number
	Sedgw		NW 1/4	SE 1/4	SE 1/4	9	_T 27 _s	R 1E E/W
Distance and direction from nearest town or city street address of well if located within city?								
15th St. and I-35 Wichita, Kansas WATER WELLOWNER: WICHITA, CITY OF								
LJ	ST. ADRESS,		N. Main	OF			Board of Agriculture, D	ivivsion of Water Resource
1	, STATE, ZIP		N. Main ita, Kansa			67203	Application Numbe	
_			4 DEPTH OF COM		L 40		VATION:	. 330003
	" IN SECTIO		Depth(s) groundw			ft.	2 ft.	3 ft.
l t			WELL'S STATIC W			FT. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	02/09/1999
	NW	NE	Pump tes	t data: W	ell water was	ft. a	ıfter hours pum	
			Est. Yield	gpm: W	ell water was	ft.	after hours pum	
Mile M	<u> </u>	E 1	Bore Hole Diameter	12 in.	to 40	ft.	and in.	to ft.
= "			WELL WATER TO	BE USED AS:	5 Public wa	•••		njection well
1	sw		1 Domestic	3 Feedlot				Other (Specify below)
			2 Irrigation	4 Industrial		_	0 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample submitted to Department?								· · · -
5 TY	DE OF CA	SING USED:	submitted				er Well Disinfected? Yes CASING JOINTS: G	
1 Stee		3 RMP (SR)		5 Wrought ir 6 Asbestos-Ce		8 Concrete tile 9 Other (Specify be		lued X Clamped Velded
2 PVC		4 ABS		7 Fiberglass		SDR-26	•	'hreaded
	_ sing Diam		in. to 20	ft., Dia		n. to	ft., Dia in.	
1		ve land surface 12		,	5.52		Wall thickness or gauge No.	to ft. .332
	•	N OR PERFORAT	_ ,			7 PVC	10 Asbestos-ceme	ent
1 Stee	el	3 Stainless Steel		5 Fiberglass		8 RMP (SR)	11 other (specify)
2 Bras	SS	4 Galvanized steel	l	6 Concrete tile		9 ABS	12 None used (o)	oen hole)
								11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREE	N-PERFO	RATION INTERVA	ALS: from 20)	ft. to 40	ft., From	ft. to	ft.
			from		ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 20 from)	ft. to 40	ft., From		ft. ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plus								
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From							ft. to ft.	
What is the nearest source of possible contamination:				ic rom		10 Livestoo	•	bandon water well
1 Septic tank 4 Lateral lines				7 Pit priv	7 Pit privy		rage 15 (Oil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lagoon			12 Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Apparent								Apparent
Direction from well? How many feet?								
FROM	TO		ITHOLOGIC LOG		FROM	1 TO	PLUGGING INTE	RVALS
0 4	8	topsoil clay						
8	20	medium f	ine gand					
20	27	coarse s						
27	30	clay						
30	40	shale						
							RECEIV	/FD
L							INTICETAL A	
							APR 0 5 19	99
-								
						BUREAU OF WATER		
	-							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No23.6								
Under	the busir	ness name of Ha	rb werr %	rump Sei	cylce	⊾யி⊆ by (signa	ature) T // 0	W
							Todd L	. starp