				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION	A/\A/	ĺ	Section Number	10	Range Number
	Sedgr		NE 1/4	SW NIW S	W 1/4	22	т 27 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
219 S. Minneapolis Wichita, Kansas								
WATER WELL OWNER: DAVID, Cliff								
RR#, ST. ADRESS, BOX#: 219 S. Minneapolis Board of Agriculture, Divivsion of Water Resource								
	Y, STATE, ZII		hita, Kans				Application Number	ir:
	TE WELL'S I	LOCATION WITH ON BOX:		MAGREED WELL	25		LEVATION:	2 0
I →		N .		iwater Encountered	1	ft.	2 ft. SURFACE MEASURED ON mo/day/yr	3 ft.
				WATER LEVEL 15 est data: Well w				11/02/1998
'	NW	NE	Est. Yield		ater was vater was	ft.	after hours pum	
1 Mile			Bore Hole Diamete	61	to	ft. ft.	after hours pum and in.	ping gpm to ft.
Įξw	/	E	WELL WATER	\ar_	Public water			njection well
1.			1 Domestic		6 Oil field wat		•	Other (Specify below)
	Zw		2 Irrigation	4 Industrial 7	Lawn and ga	rden only	10 Monitoring well	, , , , ,
			Was a chemical/ba	cteriological sample sub	mitted to De	partment? Yes	No X; If yes, n	no/day/yr sample was
		S	submitted			<u> </u>	Vater Well Disinfected? Yes	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped								
1 Stee	el	3 RMP (SR)		6 Asbestos-Cemen	t 9	Other (Specify	below) V	Velded
2 PV	C	4 ABS		7 Fiberglass			1	hreaded X
		neter 1 1/4	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height Low land surface 60 in., weight lbs. / ft. Wall thickness or gauge No.								
1			TION MATERIAL:	5 Fiberglass		PVC	10 Asbestos-cem	
1 Ste		3 Stainless Steel	-•	6 Concrete tile		RMP (SR)	11 other (specify	11/12
2 Bra		4 Galvanized ste				ABS	12 None used (o) 8 Saw cut	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed w. 1 Continous slot 3 Mill slot 6 Wire wran							9 Drilled holes	11 None (open hole)
	ered shutte	3 Mill s			wrapped			•-
		• •		7 Torch	cut		10 Other (specify) N	/A
SCREE	N-PERFO	RATION INTERV		ft.	to	ft., Fro	om ft. to	ft.
1	OD AT	EL BACK BIRDS	from	ft.		ft., Fro		ft.
	GRAV	EL PACK INTER		ft.		ft., Fr	144 44	ft.
from ft. to ft., From ft. to ft. 6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Crowt Intervals. From 0								
What is the nearest source of possible contamination:						ft. to ft. From 6 ft. to 20 ft. 10 Livestock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines				7 Pit privy	7 Pit privy		******	Oil well/Gas well
2 Sewer lines 5 Cess pool				8 Sewage lagoo	8 Sewage lagoon 12 Fertilizer			Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage None Appare								
Direction from well? How many feet?								
FROM	ТО		LITHOLOGIC LO	G	FROM	ТО	PLUGGING INTE	RVALS
	 				0	6	cement grout	_
					6	20	bentonite hole	
	 				20	25	chlorinated san	d and gravel
								
	-					 		
-								
<u> </u>			<u>-</u> .					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)11/02/1998 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No236 This Water Well Record was completed on (mo/day/yr)11/03/98								
Well (Contracto	r's License No <u>.</u>	236	This Water Well Re	cord was co	mpleted on	(mo/day/yr)11/.0.	3/98
Unde	r the busi	ness name of.Hi	arb werr &	Pump Servi	.ceIn	⊆ by (si	gnature)	. Harp
1							Joda X). JUANA