		Water Well Record	Form WWC-5	KSA 82a-1212			
LOCATION OF WATER WELL:	FRACTION	a		Section Number	Township Number	Range Number	
Sedgwick Distance and direction from peacest fow	SW 1/4	SW 1/4 S	W 1/4	28	т 27 s	$_{\rm R}$ 1E $_{\rm E/W}$	
Distance and direction frem nearest town or city street address of well if located within city? 1533 S. Emporia Wichita, Kansas							
1533 S. Empor	LAKELY, Tim	enita, kan	sas				
	533 S. Empori	a			Board of Agriculture,	Divivsion of Water Resource	
	as .						
LOCATE WELL'S LOCATION WITH		VIJERA WELL	27	ft. E	LEVATION:		
AN "X" IN SECTION BOX:		vater Encountered	1	ft.	2 ft.	3 ft.	
	WELL'S STATIC V	ATER LEVEL 13	FT. I	BELOW LAND	SURFACE MEASURED ON mo/day/yr	03/10/1999	
NWNE	Pump tes	t data: Well w	ater was	ft.	after hours pur	nping gpm	
اااوا	Est. Yield	81	ater was	ft.	after hours pur	nping gpm	
w w	E Bore Hole Diameter	35	to	ft.	and in.	to ft.	
	WELL WATER TO		Public water			Injection well Other (Specify below)	
stwste	1 Domestic 2 Irrigation		Oil field wate Lawn and ga		10 Monitoring well	Other (Specify below)	
	11					no/day/yr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded						Welded	
2 PVC 4 ABS		7 Fiberglass			•	Threaded X	
Blank casing Diameter 1 1/	4 in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surfac	,	weight		lbs. / ft.	Wall thickness or gauge No.	4	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 27 / 2							
N/A						M/A	
2 Sound to the sear (open to t						11 None (open hole)	
	5 Gauzed wrapped 6 Wire wrapped			9 Drilled holes			
1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched			••		10 Other (specify)	/A	
2 Louvered snutter 4 Key punched 7 Torch cut SCREEN-PERFORATION INTERVALS: from ft. to				ft., Fro		ft.	
	from	ft.	-	ft., Fro		ft.	
GRAVEL PACK INTERVALS: from		ft. to		ft., Fr		ft.	
	from	ft.	to	ft., Fr		ft.	
• • • • • • • • • • • • • • • • • • • •	Neat cement 2 (Cement grout	3 Bent	onite	4 Other bentonite	e hole plug	
Grout Intervals: From 0	ft. From			ft. From 3 ft. to 23 ft.			
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines					estock pens 14 Abandon water well el storage 15 Oil well/Con well		
		8 Sewage lagoon				15 Oil well/Gas well 16 Other (specify below)	
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		8 8		eticido etorogo			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard None Apparent Direction from well? How many feet?							
FROM TO		FROM	то	PLUGGING INTE	RVALS		
· ·			0	3	cement grout		
			3	23	bentonite hole		
			23	27	chlorinated sar	nd and gravel	
			 				
			 				
			 				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Mall Contracted 1:	year)03/10/	1999	and this reco	ord is true to	the best of my knowledge an	d belief. Kansas Water	
Well Contractor's License N	year)03/10/ lo236	1999 This Water Well Re	and this reco	ord is true to	the best of my knowledge an (mo/day/yr)03./.1	d belief. Kansas Water 2./99	
Well Contractor's License N Under the business name o	year)03/10/ lo236	1999 This Water Well Re	and this reco	ord is true to	the best of my knowledge an (mo/day/yr)03./.1	d belief. Kansas Water	