LIOCA	TION OF WA	TER WELL:		FRACTION	v	Vater Well Rec	cord Form WWC		KSA 82a-1212 Section Number	TN- N-		Range Numb	
LILOCA				SE 1/4	SW	1/4	SE 1/4	1	9	Township No	mber	Range Numb	
Sedqwick SE 1/4  Distance and direction frem nearest town or city street address of well if loca							DE 1/4			T 27	S	RIE	E/W
13th Street and Ohio Wichita, Kansas													
WATER WELL OWNER: WICHITA, CITY OF													
RR#,	ST. ADRESS,			Main						Boar	d of Agriculture, Di	vivsion of Water Resou	rce
CITY, STATE, ZIP CODE: Wichita, Kansa						Application Number: 990004							
	TE WELL'S L	OCATION WITH N BOX:	$\square$	EPTH OF CO						EVATION:	_	2	
†		N		pth(s) ground				ет в	ft.	2 JRFACE MEASURED	ft.	3 03/02/1	ft.
			WEL.	L'S STATIC Pump t	WAIER		⊥3 Il water was	. 1. В	ft.	after	hours pum		
'	NW	NE	Est. Y	•	gpm:		ll water was		ft.	after	hours pum		gpm gpm
1 Wile				Hole Diamete			to 40		ft.	and	in.	to	ft.
= "			WELI	L WATER TO			5 Public wa	ter s	upply	8 Air conditionin	g 11 Iı	njection well	
1 .	sw		1	Domestic	3 Fee		6 Oil field v			9 Dewatering		Other (Specify belo	)W)
			2	Irrigation	4 Ind	ustrial	7 Lawn and	gar	den only	10 Monitoring we			
Was a chemical/bacteriological sample submitted to Department? Yes										o/day/yr sample w	/as		
submitted Water Well Disinfected? Yes X No  TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Clued X Clamped													
1 Stee		3 RMP (SR)				5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded							d
2 PVC		4 ABS				erglass			R-26	below)		hreaded	
	_ sing Diam		in.	to 20	ft.	Ü		טט. n.	to	ft., Dia	in.	to ft	Ł
	-	•	L2	in.			5.52		bs. / ft.	Wall thickness or		.332	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement													
J Steel S Standess Steel						Fiberglass 8 RMP (SR) 11 other (specify)						)	
2 Bras		4 Galvanized ste		6 Con	crete tile		9 A	ABS		None used (op	•		
SCREEN OR PERFORATION OPENING ARE:						5 Gauzed wrapped				8 Saw cut 11 None (open hole)  9 Drilled holes			
1 Continuous slot 3 Mill slot 6 Wire wi 2 Louvered shutter 4 Key punched 7 Torch ci													
1		RATION INTERV					rch cut			10 Other (sp	• .		
SCREE	V-FERFO	KATIONINIEK	ALS:	from 2	0		ft. to 40		ft., Fron		ft. to		ft.
GRAVEL PACK INTERVALS: from 20					20	ft. to ft. to 40		ft., From ft., From			ft. to ft. to		ft. ft.
from							ft. to		ft., Fro		ft. to		ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug													
Grout Intervals: From 0 ft. to 20						. From	f	t. to		ft. From		ft. to	ft.
What is the nearest source of possible contamination:						7 Dit maiore			10 Livestock pens		14 Abandon water well		
1 Septic tank 4 Lateral lines						7 Pit privy 8 Sewage lagoon			11 Fuel storage 12 Fertilizer storage		15 Oil well/Gas well		
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit						9 Feedyard				ticide storage	16 Other (specify below)  None Apparent		
1	n from wel	<b>F</b>	age pit		,	7 recuyaru				How many f		Apparen	C
FROM	TO		LITHO	DLOGIC LO	G		FROM	1	TO		GGING INTER	RVALS	
0	4	topsoil											
4	15	fine sar											
15	23	coarse s	sand										
23	40	shale						-1					
				.,,									
								_					
										r. Louis - Lou			
•									-				
		***************************************											
	- Incom												
7 60	TOD A COR	DIC or : ::-	nuc	TING: TI	Thic wat	الميد م	o (4) oom -4		1 /2\ ======	ructed or /2\ rl-	aged under -	ny juriediation a	nd
										ructed, or (3) plu the best of my ki			
Well C	ontracto	's License No	23	6	This V	Vater Wel	I Record was	cor	mpleted on (r	no/day/yr)	03/0	3/99	
Under	the busin	ness name of.H	arp	Well &	P.um	p Ser	vice,	[nc	2 by (sig	nature)			
										C	Jodd D	. Harp	