, LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number		D N	
Sedgwick		NT0 C1	E 1/4	34	0.0	Range Number	
Distance and direction frem nearest town or city st	SW 1/4	NW 1/4 S	<u> </u>	34	T 27 s	R 1E E/W	
· ·		·	_				
2122 S. Grove WATER WELL OWNER: THOMI	SON, Anna	ita, Kansas	3				
	S. Grove	merre			Board of Agriculture, D	ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichi	•				r:		
LOCATE WELL'S LOCATION WITH 4		MERCO WELL	24	ft. E	LEVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	ÆLL'S STATIC W		FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	10/01/1998	
NWNE	Pump test		ater was	ft.	after hours pum		
	ıt. Yield	gpm: Well w	ater was	ft.	after hours pum		
E Bo	re Hole Diameter	inknown in. t	0	ft.	and in.	to ft.	
	ell water to 1	E USED AS: 5	Public water	r suppiy	8 Air conditioning 11 I	njection well	
X .se	1 Domestic		Oil field wa	ter supply	9 Dewatering 12 C	Other (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and g	arden only	10 Monitoring well		
		riological sample sub	mitted to De	_		io/day/yr sample was	
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		5 Wrought iron		Concrete tile		lued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement	. 9	Other (Specify		Velded	
2 PVC 4 ABS		7 Fiberglass				'hreaded	
Blank casing Diameter 1 1/4 in Casing height above land surface 60		ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height & Some I and surface 6 () in., weight lbs. / ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement						ent	
5 Fiberglass 9 DMD (SD)) 27/2	
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS		` '	11 otner (specify) N/A 12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes		
2 Louvered shutter 4 Key punched		7 Torch cut			10 Other (specify) N/A		
SCREEN-PERFORATION INTERVAL	/ Torent		ft., Fro	11	· ft.		
	LS: from from	ft. 1	-	•		ft.	
GRAVEL PACK INTERVALS: from		ft.		ft., Fro ft., Fro	/III	ft.	
	from	ft. 1		ft., Fr		ft.	
6 GROUT MATERIAL: 1 Neat cen	nent 2 C	ement grout	3 Ber	tonite	4 Other		
Grout Intervals: From 1 ft. to 24		ft. From ft. to		to	ft. From	ft. to ft.	
What is the nearest source of possible contamination:						bandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon				Other (specify below)	
3 Watertight sewer lines 6 Seepage	9 Feedyard		13 Insecticide storage None Apparent				
Direction from well? How many feet?							
FROM TO LIT	THOLOGIC LOG	7.7.1.	FROM	TO	PLUGGING INTER		
			1	24	cement grout	u siit	
			<u> </u>	47	Cement grout		
				1			
				1			
	•		ļ				
 				 	· · · · · · · · · · · · · · · · · · ·		
ļ				ļl			
 							
 			<u> </u>		761		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
was completed on (mo/day/year)		T778	and this rec	ord is true to	the best of my knowledge and	belief. Kansas Water 	
Well Contractor's License No236							
Under the business flame Of.AAMA.		<i>๛๛</i> ๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛๛	.m.m./	nw na (21)	Jadd. S	. Harp	
1					Cour L	· · · · · · · · · · · · · · · · · · ·	