Г <del>Т </del>			Water Well Record	Form WWC-5	KSA 82a-1212			
LOCATION OF WATER WELL:		FRACTION			Section Number	Township Number	Range Number	
Sedgwick		SW 1/4	SE 1/4 N	W 1/4	8	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
1801 Heiserman Wichita, Kansas  water well owner: KIMMEL, Kevin								
RR#, ST. ADRESS, BOX#: 1801 Heiserman  Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE: Wichita, Kansas						Application Number:		
LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 40 ft. ELEVATION:								
AN "X" IN S	SECTION BOX: N	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
		WELL'S STATIC WA	TER LEVEL 15	FT.	BELOW LAND SURF	FACE MEASURED ON mo/day/yr	04/30/1999	
	NWNE	Pump test	data: Well wa	ater was	ft. af	fter hours pump		
ای	V	Est. Yield	0.	ater was	ft. at	fter hours pump	ping gpm	
M M M	E	Bore Hole Diameter		• 40	ft.	and in.	to ft.	
		WELL WATER TO B		Public water			ijection well	
		1 Domestic 2 Irrigation		Oil field wate Lawn and ga		Dewatering 12 O Monitoring well	ther (Specify below)	
		Was a chemical/bacter	•			No X; If yes, mo	o/dow/we comple was	
	S	submitted	Tological sample such	mitten to 15c)	-	r Well Disinfected? Yes		
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel	3 RMP (SR)		6 Asbestos-Cement		Other (Specify bel	0.	elded	
2 PVC	4 ABS		7 Fiberglass	SI	DR-26	Ti	hreaded	
_	g Diameter 5	in. to 25	ft., Dia	in.	to	ft., Dia in.	to ft.	
	ht above land surface 1	L2 in.,	weight 2.			Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	3 Stainless Steel 4 Galvanized stee		6 Concrete tile		ABS	11 other (specify) 12 None used (ope		
	R PERFORATION OPE			d wrapped	ADS.	8 Saw cut	11 None (open hole)	
1 Continous			6 Wire w	u wrapped				
2 Louvered s			7 Torch o			10 Other (specify)		
SCREEN, PEREORATION INTERVALS: 600 0.5								
		from	ft. t		ft., From	ft. to ft. to	ft.	
GRAVEL PACK INTERVALS: from 24				to 40	ft., From	ft. to	ft.	
from ft. to					ft., From	ft. to	ft.	
_	MATERIAL: 1 Neat		ment grout	3 Bent	onite	4 Other bentonite	hole plug	
l .	vals: From 4 nearest source of possible	ft. to 22	ft. From	ft. to ft. From 22 ft. to 40 ft.  10 Livestock pens 14 Abandon water well				
1 Septic tan	-		ı: 7 Pit privy		11 Fuel stor		bandon water well	
2 Sewer line			8 Sewage lagoon		12 Fertilize	100	il well/Gas well ther (specify below)	
1	ht sewer lines 6 Seeps	-	9 Feedyard		13 Insecticide storage West		mer (speem) berom,	
Direction fro						How many feet?		
	0 1	LITHOLOGIC LOG		FROM	ТО	PLUGGING INTER	VALS	
0 2	topsoil							
2 20 20 25								
25 26		and		-				
26 40		and	-					
20   10	, mearan s	and						
							- TANK	
-								
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Well Contractor's License No236 This Water Well Record was completed on (mo/day/yr)								
Under the business name of HarpWell& PumpService,Inc by (signature)								
Todd S. Harp								