TI OCATION OF	WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212	T	T
Ľ			NTM (1)		Section Number	Township Number	Range Number
Sedgwick SW  Distance and direction frem nearest town or city street address of we			NW 1/4 S	£ 1/4	6	т 27 s	R 1E E/W
F	Riverlawn	iy sheet abditis of well it foci		Von			
		M, Wanda	Wichita	, Kali	348		
RR#, ST. ADRESS, BOX #: 2469 Riverlawn  Board of Agriculture, Divivsion of Water Resource							
CITY, STATE		hita, Kansa		Applica			er:
	L'S LOCATION WITH		APLETED WELL	40	ft. ELE	VATION:	
AN "X" IN SEC	TION BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.
		WELL'S STATIC W			BELOW LAND SUR	FACE MEASURED ON mo/day/yr	04/29/1999
<sub>N</sub>	WNE	Pump test				ıfter hours pur	
<u>e</u>		Est. Yield	91	ter was	_	after hours pur	- 0
W IWile	E	Bore Hole Diameter WELL WATER TO I	<b></b>	o 40 Public water	ft.	and in. 8 Air conditioning 11	to ft. Injection well
	k I	1 Domestic		Oil field water		-	Other (Specify below)
	(w	2 Irrigation		Lawn and ga		0 Monitoring well	(- <b>F,</b>
↓		Was a chemical/bacte	riological sample sub	mitted to De	partment? Yes	No X; If yes,	mo/day/yr sample was
	S	submitted		•	Wate	er Well Disinfected? Yes	X No
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel	3 RMP (SR)		9	Other (Specify below) Welded			
2 PVC	4 ABS		7 Fiberglass	SI	DR-26		Threaded
Blank casing D		in. to 25	ft., Dia	in.	to	ft., Dia in.	to ft.
		L2 in.,	weight 2.	<b>J J</b>		Wall thickness or gauge No. 10 Asbestos-cen	.214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)							
2 Brass 4 Galvanized steel 6 Concrete tile				9 ABS 12 None used (open hole)			
SCREEN OR	PERFORATION OPI		5 Gauze	5 Gauzed wrapped		8 Saw cut 11 None (open hole)	
1 Continous sle			6 Wire wrapped		9 Drilled holes		
2 Louvered shu	ıtter 4 Key p	unched	7 Torch	out		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 25 ft. to 40 ft., From ft. to ft.							
		from	ft. t	0	ft., From		ft.
GRAVEL PACK INTERVALS: from 24			ft. to 40		ft., From		ft.
from ft. to ft., From ft. to							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals: From 4 ft. to 22 What is the nearest source of possible contamination:			ft. From	ft. From ft. to		ft. From 22	ft. to 24 ft.
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel sto		Abandon water well
2 Sewer lines 5 Cess pool				8 Sewage lagoon		- 13	Oil well/Gas well Other (specify below)
3 Watertight sewer lines 6 Seepage pit			9 Feedyard	12 T-		ide storage	Carrier (opening season)
Direction from well? West How many feet? 90							
FROM TO		LITHOLOGIC LOG		FROM	ТО	PLUGGING INTE	ERVALS
0 4	topsoil						
4 15	clay	-			<del>                                     </del>		
15 20	fine sar						
20 30 30 40	medium s				<del>                                     </del>		
30 40	coarse s	sano	<del> </del>				
					1		
				ļ		·	
				<u> </u>	<del>                                     </del>		
					1		
				<u> </u>			
7 CONTRAC	TOR'S OR LANDOWNE	ER'S CERTIFICATION: Th	is water well was (1)	constructe	ed, (2) reconstru	ıcted, or (3) plugged under	my jurisdiction and
was complet	ted on (mo/day/year	r)	LZ.Z.Z	ind this rec	ord is true to th	e best of my knowledge an o/day/yr)0.5./0	d belief. Kansas Water 13 / 9 9
Under the h	ctor's License No Jeinese name of Ha	arp Well &	Pump Servi	cord was co	ompleted on (Mi C	o/uay/yr <i>jአ.ሐ./አ</i> ature)	. es. f. es. es. es
						Todd x	8. Harp