				Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
Distance	Sedgy		₩ SE 1/4	SW 1/4 S	W 1/4	<i>38</i> 8 7	т 27 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city?								
1440 N. St. Clair Wichita, Kansas   Water Well owner: DORR, Glen								
	ST. ADRESS	DOIL	R, Gien O N. St. C	laim			Board of Agriculture, D	ivivsion of Water Resource
1	, STATE, ZIE		hita, Kans				Application Numbe	
		LOCATION WITH		MPLETED WELL	43	ft. ELEV	ATION:	
MAN "X	" IN SECTIO	N BOX:	$\blacksquare$	water Encountered	1	ft.	2 ft.	3 ft.
1 1			WELL'S STATIC	WATER LEVEL 15	FT.	BELOW LAND SURF	FACE MEASURED ON mo/day/yr	08/27/1999
	NW	NE	Pump to	st data: Well w	ater was	ft. af	ter hours pum	• •
به			Est. Yield	gpm: Well w	ater was	ft. at	fter hours pum	ping gpm
1 Wile	-	E	Bore Hole Diameter		to 43	ft.	and in.	to ft.
"			WELL WATER TO		Public water		•	njection well
1 1	···sw··		1 Domestic		Oil field water		•	Other (Specify below)
	×		2 Irrigation	·	Lawn and ga		Monitoring well	- /
'		S	submitted	teriological sample sub	mitted to Dej			o/day/yr sample was
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Stee	1	3 RMP (SR)		6 Asbestos-Cement		Other (Specify bel		/elded
2 PVC		4 ABS		7 Fiberglass		R-26	•	hreaded
Blank ca	 sing Diam	neter 5	in. to 23	ft., Dia	in.	to i	ft., Dia in.	to ft.
		ve land surface		, weight 2 ,	35	lbs. / ft. W	all thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass 4 Galvanized steel 6 Concrete tile						ABS	12 None used (op 8 Saw cut	•
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed  1 Continuous slot 3 Mill slot 6 Wire wo						Tappea (Ferrice)		
2 Louvered shutten A Very supplied								
SOPEEN DEDECORATION INTERDIVALE.								
		MILION INVIDIO	VALS: from 2	_	to 43	ft., From	ft. to	ft.
14.					to 43	ft., From ft., From	ft. to	ft.
from ft.						ft., From	ft. to	ft. ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From							ft. to ft.	
What is the nearest source of possible contamination:						10 Livestock pens		bandon water well
1 Septic tank 4 Lateral lines 7 Pit					11 Fuel storage		- 130	oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage lago					n	12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage		
National Section of Se								
Direction from well? North How many feet? 80  FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								PVALS
0	4	topsoil					1200011011121	
4	8	clay						
8	20	medium s						
20	43	coarse s	sand					
						<u> </u>		
						<del>                                     </del>		
					1			
								A A STATE OF THE S
								VALUE
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well C	ontractor	r's License No	236	. This Water Well Re	cord was co	mpleted on (mo	/day/yr)0.8./.3.0	)/99
Under	the busir	ness name of.Жб	arp Well &	Pump Servi	ceIn	⊆ by (signat	ture)	0.0
							Todd S	. Harp