		Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick		E 1/4 SV	7 1/4	7	_T 27 s	R 1E EW
Distance and direction frem nearest town or city street address of well if located within city?						
1616 N. Charles Wichita, Kansas						
WATER WELL OWNER: CALLAHA					Paned of Agriculture D	Lines of Water Desayane
	Charles				- · · · · · · · · · · · · · · · · · · ·	ivivsion of Water Resource
	. Kansas EPTH OF 🗷 🗮 🍳		31	~ FIF	Application Numbe	*
	pth(s) groundwater		3 L 1	ft. ELE ft.	VATION: 2 ft.	3 ft.
1	L'S STATIC WATI				RFACE MEASURED ON mo/day/yr	09/21/1999
	Pump test dat				after hours pum	
Est. Y			ater was		after hours pum	- 9 Br
l ≗ l l pore t	Hole Diameter un C			ft.	and in.	to ft.
E Bore I	WAS		o Public water	_		njection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2	Irrigation 4	Industrial 7	Lawn and ga	rden only 1	0 Monitoring well	, ,
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was						
S submitted Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded						
2 PVC 4 ABS 7 Fiberglass Threaded						
Blank casing Diameter 1 1/4 in.	to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height land surface 36	in.,	weight	1	lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement						
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) N/A						II/A
			9.	ABS	12 None used (or	•
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed w					8 Saw cut	11 None (open hoie)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A						
SCREEN-PERFORATION INTERVALS: from ft. to ft., From ft. to ft.						
from		ft. t	0	ft., From		ft.
GRAVEL PACK INTERVALS: from		ft. (•			ft.
from ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug						
Grout Intervals: From 3 ft. to 8 ft. From ft. to ft. From 8 ft. to 14 ft. What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well						
1 Septic tank 4 Lateral lines		7 Pit privy	10 Livestock pens 7 Pit privy 11 Fuel storage			bandon water well
2 Sewer lines 5 Cess pool		7 Pit privy 11 Fuel storage 8 Sewage lagoon 12 Fertilizer storage		130	Oil well/Gas well	
3 Watertight sewer lines 6 Seepage pit	9 Feedyard	13 Insecticide storage				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Institute a storage None Apparent Direction from well? How many feet?						
	DLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
			0		surface silt	
			3	8 (cement grout	
			8	14 l	pentonite hole	plug
			14	31 (chlorinated san	d and gravel
				ļ		
				ļ		
				.		
			<u> </u>	ļ		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year)						
Well Contractor's License No236						
Under the business name of Harp Well & Pump Service. Inc by (signature) Todd & Harp						