	T == : ====:	Water Well Record	Form WWC-5	KSA 82a-1212		
1 LOCATION OF WATER WELL:	FRACTION		1	Section Number		Range Number
Sedgwick	NE 1/4	SW 1/4 N	1/4	9	т 27 в	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?						
	eka, NE co:	rner	Wichit	a, Kan	sas	
	Coehler, Farmers Coop Elevator, P.O. Iartel, Purina Mills, 414 East 18th Str	Box 316, Garden Plain, Kansas, 67	050			
RRW, S1. ADRESS, BOAW: D Agron	Pirner, 400 East 18th Partnership, c/c		t., Wichita, Kansas		Board of Agriculture, D	ivivsion of Water Resource
	Wichita, Kansas 67124				Application Number:	
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	depth of oth		22		LEVATION:	
A N A N SECTION BOX	Depth(s) groundw		1	ft.	2 ft.	3 ft.
	WELL'S STATIC W		FT.	BELOW LAND	SURFACE MEASURED ON mo/day/yr	10/27/1999
NE	Pump tes		ter was	ft.	after hours pum	ping gpm
	Est. Yield	G1	ater was	ft.	after hours pum	
E W	Bore Hole Diameter		0	ft.	and in.	to ft.
	WELL WATER TO		Public water			njection well
swste	1 Domestic		Oil field wat Lawn and ga		· ·	Other (Specify below)
	2 Irrigation	,	Ū	•	10 Monltoring well	(1) (
+	1	eriological sample sub	mitted to De			io/day/yr sample was
Submitted Water Well Districted? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded						
2 PVC 4 ABS		7 Fiberglass	<i>,</i> 90	Other (Specify	,	Velded Threaded
	.	•				
Blank casing Diameter 2 Casing height Box land surface	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
TYPE OF SCREEN OR PERFORA	12 in., TION MATERIAL:	weight		lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-ceme	ent
1 Steel 3 Steel 5 Fibergless 9 DMD (SD)						
2 Brass 4 Galvanized ste	el	6 Concrete tile		ABS	12 None used (or	M/A
CONTROL OF THE CONTRO				8 Saw cut	11 None (open hole)	
1 Continous slot 3 Mill s		5 Gauzed wrapped 5 Saw cut 6 Wire wrapped 9 Drilled ho			11 None (open note)	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A					/-	
SCREEN-PERFORATION INTER					11 07	
SCHEEN TENDONATION INVIER		ft. 1		ft., Fr		ft.
GRAVEL PACK INTER	from VALS: from	ft. 1		ft., Fr		ft.
GRAVEL FACE INTER	rom from	ft. ft. s	_	ft., Fr ft., Fr		ft.
6 GROUT MATERIAL: 1 Neat		Cement grout	3 Ben		om ft. to 4 Other bentonite	holo pluc
Grout Intervals: From	ft. to	ft. From				
What is the nearest source of possible contamination:					ft. From () stock pens 14 A	ft. to 22 ft. bandon water well
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel	-4	Dil well/Gas well
2 Sewer lines 5 Cess pool		8 Sewage lagoon		12 Fert	•••	On wen/Gas wen Other (specify below)
3 Watertight sewer lines 6 Seepage pit		9 Feedyard	9 Feedyard 13 Insecticide storage			, ,
Direction from well? How many feet?						
FROM TO	LITHOLOGIC LOG		FROM	то	PLUGGING INTE	RVALS
			0	22	bentonite hole	plug
			ļ			
			L.,			
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year)						
Well Contractor's License No23.6						
Under the business name of HarpWell&PumpServiceInc by (signature) Todd &. Harp						
Under the business name of Ak					gnature)	