1 LOCATION OF WATER WELL:	Water Well Record RACTION	Form WWC-5 KSA 82a-1212 Section Number		Range Number
			Township Number	
	NW 1/4 SW 1/4 NV	<b>V</b> 1/4 9	<u>т 27 s</u>	R 1E EW
Distance and direction from nearest town or city street address of well if located within city?				
18th N. and Topeka,	NE corner	<u>Wichita, Kan</u>	sas	
WATER WELL OWNER: D Terry Kochler, Farme	ers Coop Elevator, P.O. Box 316, Garden Plain, Kansas, 6 Mills, 414 East 18 <sup>th</sup> Screet, Wichita, Kansas 67124	7050		
RR#, ST. ADRESS, BOX # : D Aaron Pirner, 400 Ea	with the East 1a Street, within , Kansas 6/124 as 18th Partnership, c/o Big Bob's Carpet, 400 East 18th	St., Wichita, Kansas	Board of Agriculture, Di	vivsion of Water Resource
CITY, STATE, ZIP CODE : 0 Heiman Elevator, 1940 North Toneka Street. Wichita, Kansas 67124 D Heiman Elevator, 1940 North Toneka Street. Wichita, Kansas 67124 Application Number:				
LOCATE WELL'S LOCATION WITH 4 DEP	TH OF CHARGE VELL	27 ft. El	LEVATION:	
AN "X" IN SECTION BOX:	h(s) groundwater Encountered	1 ft.	2 ft.	3 ft.
t WELL'S	S STATIC WATER LEVEL 13	5 FT. BELOW LAND S	URFACE MEASURED ON mo/day/yr	10/27/1999
	Pump test data: Well wa		after hours pump	
Est. Yiel			after hours pum	<b>.</b>
	le Diameter unknown in. to		and in.	to fL
		Public water supply		jection well
		Oil field water supply		ther (Specify below)
Ste		Lawn and garden only	10 Monitoring weli	
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was				
submitted Water Well Disinfected? Yes X No				
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped   1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Weided				
	6 Asbestos-Cement	9 Other (Specify		elded
2 PVC 4 ABS	7 Fiberglass			hreaded X
	to ft., Dia	in. to	ft., Dia in.	to ft.
Casing height the land surface 48	in., weight	lbs. / ft.	Wall thickness or gauge No.	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement   1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)				
N/A				
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes				
<sup>2</sup> Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A				
SCREEN-PERFORATION INTERVALS:	from ft. t	o ft., Fro	•	ft.
	from ft. t			ft.
GRAVEL PACK INTERVALS:	from ft. 1			ft.
	from ft. t			ft.
6 GROUT MATERIAL: 1 Neat cement	2 Cement grout	3 Bentonite	40ther bentonite	hole plug
Grout Intervals: From ft. to	ft. From	ft. to	ft. From 3	ft. to 27 ft.
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines	7 Pit privy			
2 Sewer lines 5 Cess pool	8 Sewage lagoor	8 Sewage Lagoon 12 Fertilizer storage		ther (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage unknown				
Direction from well? How many feet?				
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS				
		0 3	compacted topso:	
		3 27	bentonite hole	
		<b>y y y</b>		<u>- ug</u>
<u>├</u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and				
was completed on (mo/day/year)				
Well Contractor's License No				
Under the business name of Harp. Well & Pump. Service, Inc. by (signature)				
Todd S. Harp				