Dunging form

		ATER WELL RECORD FORM W			
1 LOCATION OF WA			Section Number	Township Number	Range Number
County: Secgw		14 SE 14 SW 14	$\frac{35}{100}$	т <i>д</i> 7 s	R / (E)W
uistance and direction 5611 East	n from nearest town or city stre t Harry, Wichita	et address of well if located within $lpha_*$. Ks .	ıty r		
	Amoro Oil	_			
2 WATER WELL O	WNEH: 8700 India	n Creek Pkwy Su 19	90	Daniel of Amileudhine	Division of Water Bessurees
RR#, St. Address, B	Orrowland I	Park, Ks., 66210		-	, Division of Water Resources
City, State, ZIP Code			n	Application Number	:
3 LOCATE WELL'S 		F-COMPLETED WELL 219			
AN A IN SECTIO	N Depth(s) Gro	oundwater Encountered 1			
 	1 1 1 1 1 1 1 1	ATIC WATER LEVEL		•	·
NW		Pump test data: Well water was .			
1 1 1	Est. Yield .	gpm: Well water was			
₩ I	Bore Hole D	iameterin. to		ind	in. to
₹ " !	I WELL WATE	R TO BE USED AS: 5 Public	water supply		1 Injection well
sw	1 Dome				2 Other (Specify below)
	2 Irrigat				
l Li	Was a chem	ical/bacteriological sample submitted	to Department? Ye	s; If y€	es, mo/day/yr sample was sub-
<u> </u>	\$ mitted		Wat	er Well Disinfected? Yes	(No)
5 TYPE OF BLANK	CASING USED:	5 Wrought iron 8 C	oncrete tile	CASING JOINTS: GIL	ied Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement 9 O	ther (specify below) We	lded
2 PVC	4 ABS	3			readed 🔏
Blank casing diameter	r in. to	ft., Dia ii	n. to	ft., Dia	. in. to SDR . 23 ft.
Casing height above	land surface	in., weight	lbs./f	t. Wall thickness or gauge	No S.Ch . 4.0
TYPE OF SCREEN	OR PERFORATION MATERIAL	:	PVC	10 Asbestos-cer	ment
1 Steel	3 Stainless steel	5 Fiberglass 8	RMP (SR)	11 Other (specif	ý)
2 Brass	4 Galvanized steel	6 Concrete tile	ABS	12 None used (open hole)
SCREEN OR PERFO	PRATION OPENINGS ARE:	5 Gauzed wrapp	ed	8 Saw cut	11 None (open hole)
1 Continuous s	ot 3 Mill slot	6 Wire wrapped		9 Drilled holes	}
2 Louvered shu	tter 4 Key punched	7 Torch cut		10 Other (specify)	
SCREEN-PERFORAT	TED INTERVALS: From	ft. to	ft., From	n	. toft.
	From	ft. to	ft., From	n	. to
GRAVEL P	ACK INTERVALS: From	ft. to	ft., From	າ ft.	. toft.
	From	ft. to	ft., Fron	n ft.	to ft.
6 GROUT MATERIA		②cement grout , ③E	Bentonite / (4)	Other Lay	ft. to / ft.
Grout Intervals: From	om2!7ft, to . 3	ft., From	ft. to. Q	ft., From 3	ft. to
What is the nearest	source of possible antamination	n: (2)) 10 Liveste	ock pens 14	Abandoned water well
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel s	torage 15	Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertiliz	er storage 16	Other (specify below)
3 Watertight se	wer lines 6 Seepage pit	9 Feedyard	13 Insect	icide storage	
Direction from well?		·	How man		j
FROM TO	LITHOLOG			PLUGGING	INTERVALS
	Fuch Ht. Man	way was removed			
		·	1		- 104
	Type/Scillen u	as removed by d	ulling ou	UD W/8/2'00 AL	igels to 219
	1	1.0			3
	Bentonite fro	m 219 to 31			
	Caysfrom 3	<u>'- '</u>			
	Cement-from	'-0'			
	, =				

7	OD LANDOWNED CERTIFIC	ATION. This was a series of		- L	nder my jurisdiction and was
CONTRACTOR'S	OH LANDOWNER'S CERTIFIC	CATION: This water well was (1) con			
completed on (mo/da	y/year) .11-17-99		. and this recor	a is true to the best of my	knowledge and belief. Kansas
Water Well Contracto	r's License No 539	This Water Well Recor	d was completed o	in (mo/day/yr)	
	ame of JB Environ		by (signati	-77	KRUL)
INSTRUCTIONS: Use	typewriter or ball point pen. PLEASE PRI	SS FIRMLY and PRINT clearly. Please fill in bl	anks, underline or circle	the correct answers. Send top three	ee copies to Kansas Department