1 LOCATION OF WATER WELL:			FRACTION	Water Well Record	i Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
μ	Seda	rick	NW 1/4	NW 1/4 S	SE 1/4	30		110
Sedgwick NW 1/4 NE 1/4 Distance and direction frem nearest town or city street address of well if located within city? 1/4 <t< td=""><td>T 2/ S</td><td></td></t<>							T 2/ S	
1122 S. Vine Wichita, Kansas WATER WELL OWNER: COOK, Wilda								
		-					Board of Agriculture, D	ivivsion of Water Resource
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.								
WELL'S STATIC WATER LEVEL 15 FT. BELOW LAND SURFACE MEASURED ON mo/day/yr 03/08/2000								
			Pump tes		water was		-	
1	···-··NW··-	NE	Yield		water was	ft. ft.	after hours pum after hours pum	
Mile Mile			e Hole Diameter	gpm: Well 12 in.	to 40	ft.	and in.	ping gpm to ft.
<u>5</u> w	/				5 Public wate			njection well
						0	Other (Specify below)	
	sw	···	2 Irrigation		7 Lawn and g		0 Monitoring well	
			-				0	o/day/yr sample was
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was S submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Stee	el	3 RMP (SR)		6 Asbestos-Ceme	-	Other (Specify b		Velded
2 PVC	C	4 ABS		7 Fiberglass	5	× • • • • •		hreaded
Blank casing Diameter 3 () in. to ft., Dia in. to ft., Dia in. to ft.								
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No214								
TYPE	OF SCREE	N OR PERFORATION		-	7	PVC	10 Asbestos-cem	
1 Ste	1 Steel 3 Stainless Steel 5 Fiberglass					8 RMP (SR) 11 other (specify)		
2 Brass 4 Galvanized steel 6 Concrete tile 9						ABS	12 None used (oj	en hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)								
1 Conti	nous slot	3 Mill slot		6 Wire	wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 30 ft. to 40 ft., From ft. to ft.								
from ft. to ft., From ft. to								ft.
GRAVEL PACK INTERVALS: from 24 ft. to 40						ft., Fron	•	ft.
from ft. to ft., From ft. to ft.								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.								
What is the nearest source of possible contamination:10 Livestock pens14 Abandon water well								
1 Sept	ic tank	4 Lateral lin	es	7 Pit privy		11 Fuel storage 15 Oil well/Gas w		Dil well/Gas well
2 Sewe	er lines	5 Cess pool	l	8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below) 13 Investigite storage 16 Other (specify below)		Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction from well? East How many feet? 90								
FROM			HOLOGIC LOG		FROM		PLUGGING INTE	RVALS
0	4 10	topsoil		· · · · · ·		+		
<u>4</u> 10		<u>clay</u>						
10 34	34 40	medium coa shale	rse sand					
3	30	SHATE			1	+ +		
·· ·· ·						1 1		
						1		
						1		
				··· · · · · · · · · · · · · · · · · ·				
	1							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and								
was completed on (mo/day/year)								
Well Contractor's License No. 23.6. This Water Well Record was completed on (mo/day/yr)								
I Under the husiness name of Harp Well & Pump Service, TDC by (signature)								
Under the business name of Artist P								