1 LOCATION OF WATER WELL:	FRACTION	Water Well Rec	ord Form WWC-3	Section Number	Township Number	Range Number
Sedgwick	NE NE	SE 5W	SE 1/4	# 7	т 27 в	R 1E EAV
Distance and direction frem nearest town or			DE		1 1 2, 3	1 K E/W
1440 Coolidge	•	•	Michita,	Vangag		
	W, Phyllis		il Chil Ca,	Kansas		
	40 Coolidge				Board of Agriculture,	Divivsion of Water Resource
	chita,Kansa				Application Numl	her.
LOCATE WELL'S LOCATION WITH		MARCES WELL	27	n. Eli	EVATION:	
AN "X" IN SECTION BOX:		water Encountered		n. ell	2-Cl	3 ft.
1 + 1	WELL'S STATIC			BELOW HAND SO	REACE MEASURED ON mo/day/yr	04/01/2000
	Pump te		l water was		_	
NWNE	Est. Yield				after hours pur	
	Bore Hole Diameter	91	ll water was	ft.	after hours pu	
w w	WELL WATER T		to 5 Public wate	ft.	and in.	to ft. Injection well
	1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)
************************************	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well	other (speeny below)
	_				· ·	mo/dov/vr comple was
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	Was a chemical/bac submitted	teriological sample	submitted to De			mo/day/yr sample was X No
5 TYPE OF CASING USED:	Submitted	£ 33/				
1 Steel 3 RMP (SR	n	5 Wrought iron 6 Asbestos-Cen		Concrete tile Other (Specify b		Glued Clamped Welded
2 PVC 4 ABS	.,	7 Fiberglass	iiciic ,	Other (Specify B		Threaded
	for A.	_				
Blank casing Diameter 6 below basement flo Casing height above land surface f	or m. to	ft., Dia	in.	to	ft., Dia in.	to ft.
TYPE OF SCREEN OR PERFOR		, weight	7	lbs. / ft. / PVC	Wall thickness or gauge No. 10 Asbestos-cen	nent
1 Steel 3 Stainless Ste	_	5 Fiberglass		RMP (SR)	11 other (specif	(v) 37 / 3
2 Brass 4 Galvanized s		6 Concrete tile		ABS	12 None used (d	M/A
SCREEN OR PERFORATION O	PENING ARE:	5 Ca	uzed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot			6 Wire wrapped		9 Drilled holes	
2 Louvered shutter 4 Key punched			7 Torch cut		10 Other (specify) N/A	
SCREEN-PERFORATION INTE	-			A 15	•	•
			ft. to	ft., From		ft.
from GRAVEL PACK INTERVALS: from			ft. to ft., F			ſt.
GRAVEL FACE INTE	from		ft. to ft. to	ft., From ft., From		
6 GROUT MATERIAL: 1 Nea		Cement grout		itonite		
Grout Intervals: From ()	ft. to 12	ft. From			2011001120	e hole plug
What is the nearest source of possible contamination:		ic. From			ft. From 12 ft. to 16 ft. /estock pens 14 Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy	7 Pit privy			
2 Sewer lines 5 Cess pool			8 Sewage lagoon		Fertilizer storage 15 Oil well/Gas well Fertilizer storage 16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit		9 Feedyard	9 Feedyard 13 In		cide storage	(op-on)
Direction from well? East		•			How many feet? 15	
FROM TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS
			0	12 0	cement grout	
			12	16 l	centonite hole	plug
			16	27	chlorinated sar	nd and gravel
				-	. 7044	
				<u> </u>		
7 CONTRACTOR'S OR LANDOW!	NER'S CERTIFICATION: TI	his water well was	(1) constructe	ed, (2) reconstru	icted, or (3) plugged under	my jurisdiction and
was completed on (mo/day/yea	ar)04/01/	0.0	and this rec	ord is true to th	e best of my knowledge and	d belief. Kansas Water
Well Contractor's License No.	236	This Water Well	Record was co	ompleted on (me	o/day/yr)04/0	3/00
Under the business name of.	Karp Well &	.Pump Serv	ziceIn	l.C by (signa	atura)	_
					'10ad .	S. Harp