Loca	ATION OF W	ATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212			
سرا			NE 1/4	NW 1/4 S	SW 1/4	Section Number	Township Number	Range Number	
Sedgwick Distance and direction from nearest town or cit					SW 1/4	33	т 27 s	R 1E E/W	
i		. Emporia		•	,	Wichita	Kangag		
WATER WELL OWNER: BAILEY, Ralph									
RR#,	, ST. ADRESS	в, вох #: 212!	5 S. Empori	.a		Board of Agriculture, Divivsion of Water Resource			
CITY	Y, STATE, ZII	PCODE: Wic	hita, Kansa	Application Number:					
	TE WELL'S	LOCATION WITH	<b></b>	MPLETED WELL	40		VATION:		
in		N	Depth(s) groundw		. 1	ft.	2 ft.	3 ft.	
			WELL'S STATIC W Pump tes		) FT. vater was		FACE MEASURED ON mo/day/yr	04/17/2000	
'	<b>NW</b>	NE	Est. Yield		vater was water was		ifter hours pum after hours pum		
l ∰ w	,	F	Bore Hole Diameter	10	to 40	ft.	and in.	to ft.	
🖺 "	X		WELL WATER TO	BE USED AS:	5 Public water	supply		njection well	
l ı	sw		1 Domestic		6 Oil field wat	er supply	Dewatering 12 C	Other (Specify below)	
			2 Irrigation		7 Lawn and ga		0 Monitoring well		
+	Li_	S	Was a chemical/bacte	riological sample sul	bmitted to De	_		X ; If yes, mo/day/yr sample was	
5 TY	PE OF CA	ASING USED:	submitted				er Well Disinfected? Yes		
1 Stee		3 RMP (SR)		5 Wrought iron 6 Asbestos-Cemen		Concrete tile Other (Specify be		lued X Clamped /elded	
2 PV		4 ABS		7 Fiberglass		Other (specify be DR = 26	•	veided hreaded	
			in. to 30	ft., Dia	in.	JR - 20 to	ft., Dia in.	to ft.	
I		•	L2 in.,	weight 2			Vall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement									
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								)	
2 Brass 4 Galvanized steel 6 Concrete tile					9	9 ABS 12 None used (open hole)			
					ed wrapped				
	nous siot ered shutte	3 Mill sl	-		wrapped		9 Drilled holes		
		<b>J</b> F		7 Torch			10 Other (specify)	_	
SCREE	N-PERFO	RATION INTERV			to 40	ft., From	ft. to	ft.	
	GRAV	EI DACK INTERI	from VALS: from 24	ft.	to 40			ft.	
GRAVEL PACK INTERVALS: from 2				t. ft.		ft., From ft., From	ft. to ft. to	ft. ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug									
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.									
What is the nearest source of possible contamination:						10 Llvestoc	k pens 14 A	14 Abandon water well	
1 Septic tank 4 Lateral lin				05		11 Fuel sto	130	15 Oil well/Gas well	
2 Sewe		5 Cess	•	8 Sewage lagoo	n	12 Fertilizer storage 13 Insecticide storage		ther (specify below)	
o seepage pit 7 recuyatu									
Direction from well? West FROM TO LITHOLOGIC LOG					FROM	то	How many feet? 90 PLUGGING INTER	PVALS	
0	4	topsoil			T ANOM	10	TECGGING INTER	VALS	
0 4 10 20	10	clay							
10	20	fine san							
20	37		oarse sand			ļ			
37	40	shale				ļ			
					<u> </u>				
						<del>                                     </del>	*****		
					<u></u>				
7 CO	NTRACTO	)R'S or landowne	R'S CERTIFICATION: Th	is water well was (1	) constructe	d, (2) reconstru	cted, or (3) plugged under m	y jurisdiction and	
was c	ompleted	on (mo/day/year)	)04/17/	0.0	and this reco	ord is true to the	best of my knowledge and	belief. Kansas Water	
Well C	ontractor	i's License No	arp Well &	This Water Well Re	cord was co	empleted on (mo	o/day/yr)	<u>//.u.u</u>	
Ulluel	lite busii	less fidifie of.AAM	Am &	*		M by (signa	Todd S	S. Harp	