T		ED A CTION	Water	Well Recor	d Form WWC-5	KSA 82a-1212		i	
<u>. </u>	N OF WATER WELL:	FRACTION				Section Numbe	1	~ l	Range Number
	edgwick	SW 1/4	NW		SW 1/4	31	т 22/2	s d/	R 1E E/W
	direction frem nearest town or city	y street address of well if loc							
	8 Rita RWELLOWNER: DAVI	ra Deb	Wi	<u>chit</u>	ca, Kan	sas			
		IS, Bob B Rita					Boa	rd of Agriculture, Div	ivsion of Water Resource
		nita, Kansa						Application Number:	
1	VELL'S LOCATION WITH	DEPTH OF CAN	MARIER	WELL	29	n. E	LEVATION:		
	SECTION BOX:	Depth(s) groundw			1	n.	2	ſt.	3 ft.
. т Г		WELL'S STATIC W	ATER LEV	VEL 1	0 FT.	BELOW LAND	SURFACE MEASUREI	ON mo/day/yr	06/21/2000
	NE	Pump tes	t data:	Well	water was	ſt.	after	hours pump	
		Est. Yield	gpm:	Well	water was	ft.	after	hours pump	ing gpm
M M	E	Bore Hole Diameter	•	in.	to	ft.	and	in.	to ft.
⁻ .		WELL WATER TO			5 Public water		8 Air conditioni		jection well
		1 Domestic	3 Feedlo		6 Oil field wa		9 Dewatering		ther (Specify below)
		2 Irrigation			7 Lawn and g		10 Monitoring w		/4/
	S	Was a chemical/bacte submitted	riological s	ample si	ubmitted to De	-	s No Vater Well Disinfec		/day/yr sample was X No
5 TYPE	OF CASING USED:	Submitted	5 Wroug	ght iron		Concrete tile	CASING 3		1ed Ciamped
1 Steel	3 RMP (SR)		6 Asbest	-		Other (Specify		0	elded
2 PVC	4 ABS		7 Fiberg	lass		(- F ,	,,		readed
Blank casin	g Diameter 1 1/4	in. to	ft.,	Dia	in.	to	ft., Dia	in.	to ft.
	ht and surface 6	0 in.,	-	eight		lbs. / ft.	Wall thickness o		
	SCREEN OR PERFORAT	ΓΙΟΝ MATERIAL:	E Ethanala			PVC		Asbestos-cemer	nt
1 Steel	3 Stainless Steel		5 Fibergla			RMP (SR)		1 other (specify)	N/A
2 Brass	4 Galvanized stee		6 Concret			ABS		2 None used (ope	n hole) 11 None (open hole)
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot			5 Gauzed wrapped						
2 Louvered	6 Wire wrapped				9 Drilled holes 10 Other (specify) N/A				
	7.1			7 Torc			•	247	
SCREEN-P	ERFORATION INTERV				. to	ft., Fr		ft. to	ſt.
from GRAVEL PACK INTERVALS: from			ft. to ft. to			ft., From		ft. to	ft.
GRAVEL FACK INTERVALS: From			ft. to			ft., From ft., From		ft. to ft. to	ft. ft.
6 GROUT	MATERIAL: 1 Neat of		ement grou			tonite	4 Other	10. 10	
Grout Inter	vals: From O	ft. to 29	ft. Fr	om	ſt.	to	ft. From	•	ft. to ft.
What is the nearest source of possible contamination:					10 Livestock pens		14 Abandon water well		
1 Septic tank 4 Lateral lines			7 Pit privy			11 Fuel storage		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon			12 Fertilizer storage 13 Insecticide storage		16 Other (specify below)	
	ht sewer lines 6 Seepa	ige pit	9 Fee	edyard		15 Ilise	cucide storage	None	Apparent
Direction fr FROM		LITHOLOGIC LOG			FROM	ТО	How many f		LAT C
TROM	10	ETTHOLOGIC LOG			0	29	cement q	COULT	VALS
					-		comerc g	1040	
			~~~~						
	***************************************		VIT						
				<del></del>					
						-			
	***				_		nu-1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1		
				*-					**************************************
					-				
7	L GEORGE		4	- 11	40	. 1 (6)	44		
	RACTOR'S or Landowner pleted on (mo/day/year)								
Well Con	pieted on (mo/day/year) tractor's License No	236	m.w Thic Wata		, and this rec Record was a	oru is true to ompleted on	i ille best of my Ki (mo/dav/vr)	06/23	/00
	e business name of.Ha								_
Unider till	JIIICJJ HUHIC VIJAM	g					g	Todd S	. Harv