1 LOCATION OF WATER WELL:	FRA	CTION	Wa	ter Well Kec	ord Form WV	1	Section Number	Township Number	Range Number	
Sedgwick	s	E 1/4	NE	1/4	NW 1/	.	8	₁ 27 s	R 1E E/W	
Distance and direction frem nearest town or c					2177	<u></u>		1 27 3	1 R 22 E/W	
2007 N. Arkansas Wichita, Kansas water well owner: ST. PATRICK CHURCH										
RR#, ST. ADRESS, BOX#: 2007 N. Arkansas Board of Agriculture, Divivsion of Water Resource										
CITY, STATE, ZIP CODE: Wic			Application Number:							
LOCATE WELL'S LOCATION WITH		H OF CO		WELL	. 21		ft. ELI	EVATION:		
AN "X" IN SECTION BOX:		s) groundw	~~				ft.	2 ft.	3 ft.	
	1 '	STATIC W			11	FT.		RFACE MEASURED ON mo/day/yr	07/27/2000	
	WEEL S	Pump tes			L L l water was			after hours pur		
NW NE	Est. Yield	-	gpm:		l water was		ft.	after hours pu		
w E	Bore Hole	Diameter	•	in	to		n.	and in.		
E		ATER W	S used) AS:	5 Public w	ater			Injection well	
	1 Don	nestic	3 Feed	llot	6 Oil field				Other (Specify below)	
sw se	2 Irri		4 Indu					10 Monitoring well	(-1,	
	1 '		riologica	al samnla		-	partment? Yes	8	mo/day/yr sample was	
S	submitte		eriologica	u sampie	submitted to	De	-		X No	
5 TYPE OF CASING USED:	Sublitte	<u> </u>	£ W-		_	•	Concrete tile		Glued Clamped	
1 Steel 3 RMP (SR)				ought iros estos-Cen			Other (Specify b		Welded	
2 PVC 4 ABS							alvanize		Threaded X	
Blank casing Diameter 6	in. to					_		u	A .	
Casing height above land surface		-	ſt.,	Dia		in.	to lbs. / ft.	ft., Dia in. Wall thickness or gauge No.	to ft.	
TYPE OF SCREEN OR PERFORA		in., ΓERIAL:		weight		7	PVC	10 Asbestos-cen	nent	
1 Steel 3 Stainless Steel			5 Fiber	glass			RMP (SR)	11 other (speci	^{fy)} N/A	
2 Brass 4 Galvanized steel				rete tile		9	ABS	12 None used (c	· N/A	
		r.		5 G o	uzed wronn			8 Saw cut	11 None (open hole)	
SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot				5 Gauzed wrapped 6 Wire wrapped				9 Drilled holes		
)		••					- / -			
1				7 Torch cut					I/A	
SCREEN-PERFORATION INTER	VALS:	from			ft. to		ft., From	n ft. to	ft.	
from			ft. to				ft., From		ft.	
GRAVEL PACK INTERVALS: from			ft. to				ft., Fron		•••	
COOUT MATERIAL 1 Neet	cement	from	ement gi		ft. to	D	ft., Fron			
6 GROUT MATERIAL: 1 Neat Grout Intervals: From		2 (Ü				tonite		e hole plug	
Grout Intervals: From ft. to What is the nearest source of possible contamination:			ft. From ft.			ft. t	to 10 Livesto	ft. From 3	ft. to 12 ft. Abandon water well	
1 Septic tank 4 Lateral lines			7 Pit privy				11 Fuel st			
2 Sewer lines 5 Cess pool			8 Sewage lagoon					13	Oil well/Gas well Other (specify below)	
3 Watertight sewer lines 6 Seepage pit			0 0					secticide storage		
Direction from well? North LITHOLOGIC LOG			FROM			M	TO	How many feet? 25 TO PLUGGING INTERVALS		
		0.0 200			0			cement	ACTADO	
					3			bentonite hole	plug	
					12			chlorinated same		
								<u> </u>	314,91	
					,					
		-								

									AND AND ASSESSMENT OF THE PARTY	
									THE RESERVE THE PARTY OF THE PA	
					į.					
7 CONTRICTORS			i		. (4)			moted or (2) when and the term	my juriodistics and	
7 CONTRACTOR'S OR LANDOWNI was completed on (mo/day/yea	ER'S CERTIFIC	CATION: Th フ/クワ/	is water ∩∩	well was	s (1) constr	ucte	eu, (z) reconstr	ucted, or (3) plugged under	my jurisdiction and	
Well Contractor's License No	236	.//f4.//	M.W	ator Mol	and this	rec	ona is true to ti completed on /~	ne best of my knowledge an	12/00	
I the desired the business name of Harn Well & Pump Service, Inc. by (signature)										
Chac the business name of MA								Todd	S. Harp	