

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Sedgwick		NE 1/4 NE 1/4 NW 1/4	36	T 27 S	R 1 EW
Distance and direction from nearest town or city street address of well if located within city? Harry & Edgemor Street, Wichita, KS. 5601 E. Harry, Wichita, K					
2 WATER WELL OWNER: Walgreen's Inc.					
RR#, St. Address, Box # : Harry & Edgemor			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, KS.			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 20' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 13' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 13.20 ft. below land surface measured on mo/day/yr 5-24-00 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 8 1/2" in. to 20' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No No			
		5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. Clamped. 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded 2 PVC 4 ABS 7 Fiberglass Threaded X Blank casing diameter 2.375 in. to 10' ft. Dia. in. to ft. Dia. in. to SDR 13 ft. Casing height above land surface Flush Mt in. weight lbs./ft. Wall thickness or gauge No. SCH 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From 20' ft. to 10' ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20' ft. to 8' ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 8' ft. to 3' ft. From 3' ft. to 0' ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? North North East How many feet? 325'					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	7	Brn clay-silty clay, moist, no odor, firm.			
7	15.5	Lt gray to green gray silty clay, moist, firm, faint-no odor, trace of mottling.			
15.5	20	Gray fine-coarse sand, wet, strong odor, poorly sorted w/some yellow brn clay stringers.			
					Fl mt ok'd by Don Taylor
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-24-00 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 539 This Water Well Record was completed on (mo/day/yr) 6-12-00 under the business name of JB Environmental Drilling by (signature) James Becker					