1 LOCATION OF WATER WELL:	FRACTION	Water Well Reco	rd Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number
Sedgwick	SE 1/4	SW 1/4	SE 1/4	9	077	1 17
Distance and direction frem nearest town or city			DE M	J	T 2/ s	R IE EW
13th N. & Ohio		Wid	chita,	Kangag		
	ITA, CITY		<u> </u>	- Caribab		
RR#, ST. ADRESS, BOX #: 455	N. Main				Board of Agriculture, D	ivivsion of Water Resource
CITY, STATE, ZIP CODE: Wich	<u>ita, Kansa</u>			67202	Application Numbe	r: 990004
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF	D WELL	40		EVATION:	
N N	Depth(s) groundw	_	1	ft.	2 ft.	3 ft.
	WELL'S STATIC W		~		RFACE MEASURED ON mo/day/yr	08/18/2000
NWNE	Pump tes Est. Yield		water was	ft.	after hours pum	
#	Bore Hole Diameter	gpm: Well in.	water was	ft. ft.	after hours pum	- 0
E L	VELL WATER		5 Public water		and in. 8 Air conditioning 11 In	to ft. njection well
1. 1.	1 Domestic	3 Feedlot	6 Oil field was		•	Other (Specify below)
SW SE	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring weli	(openy selon)
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was						
S submitted Water Weli Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped						
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded						/elded
2 PVC 4 ABS		7 Fiberglass			Т	hreaded
	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height land surface 3 (TYPE OF SCREEN OR PERFORAT		weight	~	lbs. / ft.	Wall thickness or gauge No. 10 Asbestos-ceme	ant.
1 Steel 3 Steinlere Steel 5 Fiberglass 8 RMP (SD) 11 of the (consider)						
2 Brass 4 Galvanized steel	6 Concrete tile	N/A			M/ A	
SCREEN OR PERFORATION OPEN	5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire wrapped			9 Drilled holes	
2 Louvered shutter 4 Key punched		7 Torch cut			10 Other (specify) N/A	
SCREEN-PERFORATION INTERVA		. to	ft., From	/	r.	
]	from		. to	ft., Fron		ft.
GRAVEL PACK INTERVALS: from		ft. to		ft., Fron	-	ft.
from ft. to ft., From ft. to					n	
6 GROUT MATERIAL: 1 Neat ce		ement grout	3 Ben	tonite	4 Other bentonite	hole plug
Grout Intervals: From 3 ft. to 8 What is the nearest source of possible contamination:		ft. From ft. to			ft. From 8 ft. to 12 ft.	
1 Septic tank 4 Lateral lines		·		10 Livesto	vestock pens 14 Abandon water well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon			130	oil well/Gas weil
3 Watertight sewer lines 6 Seepage pit					ecticide storage	
Direction from well? None Apparent How many feet?						
FROM TO L	THOLOGIC LOG		FROM	TO	PLUGGING INTER	RVALS
ļ			0	3	surface clay and	d silt
			3		cement grout	
	1400		8		bentonite hole	
			12	40	chlorinated san	d and gravel
	7.			 	***************************************	
				 		
				·		
		-				
· · · · · · · · · · · · · · · · · · ·		····				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and						
was completed on (mo/day/year)						
Well Contractor's License No236						
Todd S. Harp						