LOCATIO	NOF WATER WELL.	FRACTION	Water Well Reco	rd Form WWC-5	Section Number		T	
						Township Number	Range Number	
	edgwick	SW 1/4		SE 1/4	9	т 27 s	R 1E EW	
Distance and	l direction frem nearest town or c	ity street address of well if lo	cated within city?					
13t	h N. & Ohio		Wie	chita,	Kansas			
		HITA, CITY						
RR#, ST. ADRESS, BOX#: 455 N. Main						Board of Agriculture, Divivsion of Water Resource		
		hita, Kans	s 67202			Application Number: 990004		
T	WELL'S LOCATION WITH		MAGENEELL	40		EVATION:	. 330004	
	WELL'S LUCATION WITH			_			2	
<b>│ 。 ┌</b>	N	1 ' ''	water Encountered	1	ſt.	2 ft.	3 ft.	
		WELL'S STATIC V		.3 FT.	. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	08/18/2000	
] ] [	NWNE	Pump te	st data: Well	water was	n.	after hours pum	ping gpm	
6,		Est. Yield	gpm: Well	water was	ſt.	after hours pum	ping gpm	
M K	F.	Bore Hole Diameter	_ in.	to	ſt.	and in.	to ft.	
= "		WELL WATER	TE USED AS:	5 Public wate	r supply	8 Air conditioning 11 In	njection well	
		1 Domestic	3 Feedlot	6 Oil fleld wa	•	•	Other (Specify below)	
l I. l'''			4 Industrial	7 Lawn and g		10 Monitoring well	rener (opeciny below)	
		2 Irrigation		_	•	· ·		
+		Was a chemical/bact	eriological sample s	ubmitted to De	-		io/day/yr sample was	
<u> </u>	3	submitted			Wa	ater Well Disinfected? Yes	X No	
5 TYPE	OF CASING USED:		5 Wrought iron	8	Concrete tile	CASING JOINTS: G	lued Clamped	
1 Steel	3 RMP (SR)		6 Asbestos-Ceme	ent 9	Other (Specify b	below) W	Velded	
2 PVC	4 ABS		7 Fiberglass		, - •	T	'hreaded	
	ng Diameter 8	in. to	Ü					
	ght and surface	• •	ft., Dia	in.	to	ft., Dia in.	to ft.	
			, weight	_	lbs. / ft.	Wall thickness or gauge No.	···•	
	SCREEN OR PERFORA		E Tibovalage		PVC	10 Asbestos-ceme		
1 Steel	3 Stainless Steel		5 Fiberglass		RMP (SR)	11 other (specify)	) N/A	
2 Brass	4 Galvanized ste	el	6 Concrete tile	9	ABS	12 None used (op	en hole)	
SCREEN O	OR PERFORATION OP	ENING ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)	
1 Continou	ıs slot 3 Mill s	dot		e wrapped		9 Drilled holes		
2 Louvered		ounched					<i>t</i> =	
İ			7 Torc			10 Other (specify) N/		
SCREEN-P	PERFORATION INTER	VALS: from	U	ft. to ft., Fr		n ft. to	ft.	
		from	n	t. to	ft., Fron	m ft. to	ft.	
GRAVEL PACK INTERVALS: from			ft. to		ft., Fron	m ft. to	ſt.	
		from		t. to	ft., Fron	m ft. to	ft.	
6 GROUT	Γ MATERIAL: 1 Neat	cement 2	Cement grout	3 Bei	ntonite	40ther bentonite	hole plug	
Grout Intervals: From 3 ft. to 8			O From	ft. From ft. to				
What is the nearest source of possible contamination:			ir Liom			ft. From 8 ft. to 14 ft.		
1 Septic ta		7 Pit privy		11 Fuel st	torono			
			- ·			13 Ou well Gas well		
2 Sewer lines 5 Cess pool			12.7			natialdo atomaso		
ľ	-	page pit	9 Feedyard		15 Hisecti	None	Apparent	
Direction fr						How many feet?		
FROM	ТО	LITHOLOGIC LOG		FROM	TO	PLUGGING INTER		
				0	3	surface clay and	d silt	
				_   3	8	cement grout		
				8		bentonite hole	plua	
				14		chlorinated san		
				1 4 3	130	chiorinated Ban	u and graver	
					<del></del>			
					_			
7 CONTI	PACTORIS OR LANDOWNIE	ene gentiera troy. Ti	nie water well was	(1) construct	od (3) recensts	ructed, or (3) plugged under m	av juriodiation and	
Was some	NACION SUKLANDUWNE	A NA/18/	UU Warei Meii Mas	( I) Construct	eu, (z) reconsu	he best of my knowledge and	belief Kanaga Matan	
Was Colli	pieted on (mo/day/year	236		anu tins ret		(4	I / N N	
Well Con	tractor's License No	236	This Water Well F	Record was c	ompleted on (n	no/day/yr)	L/QQ	
Well Con	pieted on (mo/day/year itractor's License No e business name of.从i	236	This Water Well F	Record was c	ompleted on (n	no/day/yr)	1/00	