1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
		GW G				l	
Sedgwick	SE 1/4		E 1/4	9	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city? 13th N. & Ohio Wichita, Kansas							
13th N. & Ohio			hita,	Kansas		· · · · · · · · · · · · · · · · · · ·	
	HITA, CITY N. Main	OF			Posed of Academiana Di	-tt W-t D	
			Board of Agriculture, Divivsion of Water Resource				
CITY, STATE, ZIP CODE: Wic				Application Number: 990004			
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		1930 D WELL	40		EVATION:		
N Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
	WELL'S STATIC W		•	BELOW LAND SUI	RFACE MEASURED ON mo/day/yr	08/18/2000	
NE	Pump tes	t data: Well w	vater was	ſt.	after hours pump	ping gpm	
ا ا ا	Est. Yield	gpm: Well v	vater was	ft.	after hours pum	ping gpm	
E W	Bore Hole Diameter		to	ſt.	and in.	to ft.	
"	WELL WATER **	BE USED AS:	Public water	r supply	8 Air conditioning 11 Ir	ıjection well	
swswsae	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12 O	ther (Specify below)	
	2 Irrigation	4 Industrial	7 Lawn and g	arden only 1	10 Monitoring well		
	Was a chemical/bacte	eriological sample sul	bmitted to De	epartment? Yes	No X ; If yes, me	o/day/yr sample was	
S	submitted			Wat	ter Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cemen	ıt 9	Other (Specify b	elow) W	elded	
2 PVC 4 ABS		7 Fiberglass			T	hreaded	
Blank casing Diameter 8	in. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height as a land surface	36 in.,	weight			Wall thickness or gauge No.	200	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement						nt	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) NT / N						N/A	
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)							
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped				8 Saw cut	11 None (open hole)		
1 Continous slot 3 Mill s	6 Wire wrapped			9 Drilled holes			
2 Louvered shutter 4 Key p		7 Torch cut 10 C			' x		
SCHEEN BEDEODATION INTERVALS.							
				ft., From		ñ.	
from		ft. to		ft., From		ft.	
GRAVEL PACK INTERVALS: from		ft. to ft. to		ft., From		ſt.	
6 GROUT MATERIAL: 1 Neat	cement 2 C			ft., From		aa	
Grout Intervals: From 3		Cement grout	3 Ber	itonite		hole plug	
Grout Intervals: From 3 ft. to 8 What is the nearest source of possible contamination:		ft. From ft. to			ft. From 8	ft. to 12 ft.	
1 Septic tank 4 Lateral lines				10 Livesto 11 Fuel sto	2772	bandon water well	
- A Lince in inites		8 Sewage lagoon			130	15 Oil well/Gas well	
5 Ccss poor					acticide storage		
None Apparent							
Direction from well? How many feet? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS							
FROM 10	LITHOLOGIC LOG		FROM	3 4			
			0		surface clay and	1 SIIC	
			3		cement grout	- 7	
			88		bentonite hole		
			12	40	chlorinated sand	d and gravel	
	AT-14 (F - 16)						
				-			
		www.					
				ļl			
			- 	ļ			
			ļ			<u></u>	
					7		
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No23.6							
Index the business name of HATD Well & Pump Service. Inc. by (signature)							
Todd S. Harp							