1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212	<u> </u>	· · · · · · · · · · · · · · · · · · ·	
	Ī			Section Number	Township Number	Range Number	
Sedgwick Distance and direction from peacest town on cit	SW 1/4	NW 1/4 SI	€ 1/4	6	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?							
1931 W. 24th N. Wichita, Kansas WATER WELL OWNER: HILL, F.L.							
RR#, ST. ADRESS, BOX#: 1931 W. 24th N. Board of Agriculture, Divivsion of Water Resource							
CHTY STATE GODD TILL I - TP							
LOCATE WELL'S LOCATION WITH	4 DEPTH OF COM		40	A FIF	Application Numb	er:	
AN "X" IN SECTION BOX:	Depth(s) groundwa		1	ft. ELE ft.	.varion: 2 ft.	3 ft.	
	WELL'S STATIC WA		_		RFACE MEASURED ON mo/day/yr	08/31/2000	
	Pump test				after hours pun		
NE	Est. Yield	***************************************	ater was		after hours pun		
e William E	Bore Hole Diameter		• 40	ft.	and in.	to ft.	
= "	WELL WATER TO B		Public water			Injection well	
X ste	1 Domestic		Oil field wat		9 Dewatering 12	Other (Specify below)	
	2 Irrigation	4 Industrial 7	Lawn and ga	rden only 1	0 Monitoring well		
	Was a chemical/bacter	riological sample subi	mitted to Dep	partment? Yes	No X; If yes, r	no/day/yr sample was	
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (Specify below) Welded						Welded	
2 PVC 4 ABS		7 Fiberglass	SI	DR-26	•	Threaded	
Blank casing Diameter 5	in. to 30	ft., Dia	in.	to	ft., Dia in.	to ft.	
	in.,	weight 2.			Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)							
1 Day 1 C 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1					11 other (specif	•	
CONTRACT OF THE CONTRACT OF TH				OG (CPC)			
1 Continous slot 3 Mill sl		l wrapped		9 Drilled holes	11 Noise (open noie)		
2 Louvened shutten 4 Very marked							
SCOPEN DEDECORATION INTERNALS.							
it to ±0 it, From it to						ft.	
GRAVEL PACK INTERVALS: from 24		ft. to ft. to 40		ft., From		ft.	
from		= •		ft., From ft., From		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug							
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.							
What is the nearest source of possible contamination:				10 Livesto		Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto	orage 15	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon			er storage 16	16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit		9 Feedyard	yard 13 Insecticide storage		cide storage		
Direction from well? East How many feet? 15							
	LITHOLOGIC LOG		FROM	то	PLUGGING INTE	RVALS	
0 4 topsoil 4 15 clay	7.0			 			
4 15 clay 15 25 fine san							
	oarse sand						
	Oarse saild						
					- W-V-2-W-W-V-		
				<u> </u>	#_ W		
					. 17701-20-00-		
					,,		
		15000					
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No		This Water Well Red	ord was co	mpleted on (m	o/day/yr)0.9./.0	1/00	
Under the business name of Harp Well & Pump Service. Inc. by (signature) Todd S. Harp							
1					Loui .	א ואט ה	