LOCATION OF W	TED WELL	FRACTION	Water Well Rec	ord Form WWC-	Section Number	Township Number	Range Number	
				G74			1	
Sedgv		SW 1/4	NE 1/4	SW 1/4	4	T 27 s	R 1E E/W	
Distance and direction frem nearest town or city street address of well if located within city?								
From 21	lst & Mosle	y, $3/8$ m	N. & 1/	8 m. W.	Wic	hita, KS.		
WATER WELL		AT CONSTR						
RR#, ST. ADRESS		W. Harry		Board of Agriculture, Divivsion of Wa			ivivsion of Water Resource	
CITY, STATE, ZIP CODE: Wichita, Kansa			s 67209			Application Number:		
LOCATE WELL'S			HAR BOWELL	. 30		EVATION:		
AN "X" IN SECTIO	N DOV.	Depth(s) groundw	U U		n.	2 ft.	3 ft.	
] +		, .				RFACE MEASURED ON mo/day/yr	09/19/2000	
1 1 1 1		ELL'S STATIC W						
NW	NE	Pump tes		l water was	ſt.	after hours pum	ping gpm	
		t. Yield		li water was	ft.	after hours pum	ping gpm	
w w	E Boi	re Hole Diameter	15 in.	to	ft.	and in.	to ft.	
-	WI	ELL WATER TO	SE USED AS:	5 Public wate	r supply	8 Air conditioning 11 I	njection well	
		1 Domestic	3 Feedlot	6 Oil field w	iter supply	9 Dewatering 12 C	Other (Specify below)	
Sw	3	2 Irrigation	4 Industrial	7 Lawn and	garden only	10 Monitoring well	a stockyand H2O	
		as a chemical/hacte	riological sample	submitted to D	enartment? Ves		io/day/yr sample was	
							• •	
TUDE OF CASING LISED								
Swinght from . a Concrete tile Choire of Children Champen								
- Contract (opening sectors)								
2 PVC	4 ABS		7 Fiberglass			1	`hreaded	
Blank casing Diam	NL-1	. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height a		in. ,	weight		lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREE	N OR PERFORATIO	ON MATERIAL:		7 PVC 10 Asbestos-cement				
1 Steel 3 Stainless Steel 5 Fiberglass					8 RMP (SR) 11 other (specify) N/A			
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								
SCREEN OR PE	5 Ga	uzed wrapped		8 Saw cut 11 None (open hole)				
1 Continous slot 3 Mill slot			6 Wire wrapped			9 Drilled holes		
2 Louvered shutte	••				/-			
			7 101	rch cut		N	/A	
SCREEN-PERFO	RATION INTERVAL	ft. to		ft., Fron	ft. to	ft.		
from from			ft. to		ft., Fron	n ft. to	ft.	
GRAVEL PACK INTERVALS: from				ft. to	ft., Fron	n ft. to	ft.	
		from		ft. to	ft., Fron	n ft. to	ft.	
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 3 ft. to 8 ft. From ft. to ft. From 8 ft. to 15 ft.								
What is the nearest source of possible contamination:						estock pens 14 Abandon water well		
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel st	orage 15 (15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon		12 Fertili		16 Other (specify below)	
3 Watertight sewer lines 6 Seepage pit						ecticide storage		
None apparent								
FROM TO		HOLOGIC LOG		FROM	то	How many feet? PLUGGING INTE	WATO	
TAOM TO		HOLOGIC LOG						
			· · · · · · · · · · · · · · · · · · ·	3		surface clay an cement grout	G SITL	
							1	
				8		bentonite hole		
				15	30	chlorinated san	d and gravel	
							Marian Marian Company of the Salama and the Marian Company of the Salama Company of the	
	1/44	734						
 								
7 CONTRACTO	R'S or landowner's o	ERTIFICATION: Th	is water well was	(1) construct	ed, (2) reconstr	ucted, or (3) plugged under n	ny jurisdiction and	
was completed on (mo/day/year)								
Well Contractor's License No236								
Under the business name of Harp Well & Pump Service. Inc. by (signature) Todd S. Harp								
Under the busin	ess name of.スステネネム₺	×	*·*****	አ ጕሥሥ ነው	AM by (sign	ature)	2 11	