1 LOCATION OF WATER WELL:	FRACTION	Water Well Recor	rd Form WWC-5	KSA 82a-1212 Section Number	TII- NI	T	
Sedgwick		NTM	aw		Township : Value	Range Number	
Distance and direction frem nearest town or city	SW 1/4		SW 1/4	17	_T 27 _S	R 1E E/W	
	street addition of well it for	•	77				
828 Gilman WATER WELL OWNER: KENT	, Jim	Wichita,	Kansas				
	Gilman				Board of Agriculture, J	Divivsion of Water Resource	
	nita, Kansa	as		67203	Application Numb		
LOCATE WELL'S LOCATION WITH		MELL WELL	26		LEVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundw	vater Encountered	1	, ft.	-2 ft	3 ft.	
	WELL'S STATIC W	ATER LEVEL 1	3 гт.	BELOW LAND	ORFACE MEASURED ON mo/day/yr	02/14/2001	
NE	Pump tes	t data: Well	water was	ſt.	after hours pun	• •	
	Est. Yield	gpm: Well	water was	n.	after hours pun		
1 5 "	Bore Hole Diameter	as in.	to	ft.	and in.	to ft.	
	WELL WATER TO		5 Public water		-	Injection well	
	1 Domestic	3 Feedlot	6 Oil field was		•	Other (Specify below)	
	2 Irrigation	4 Industrial	7 Lawn and g		10 Monitoring well		
	Was a chemical/bacte submitted	eriological sample su	ubmitted to De	•		no/day/yr sample was	
5 TYPE OF CASING USED:	Submitted	f Wassaht inon			/ater Well Disinfected? Yes CASING JOINTS: 0		
1 Steel 3 RMP (SR)		5 Wrought iron 6 Asbestos-Ceme		8 Concrete tile CASING JOINTS: Glued Clamped 9 Other (Specify below) Welded			
2 PVC 4 ABS		7 Fiberglass	-	Outer (opening	,	rhreaded	
Blank casing Diameter 1 1/4	in, to	ft., Dia	in.	to	ft., Dia in.	to R.	
Casing height above land surface 6		weight		lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORAT	Ü	7 PVC 10 Asbestos-cement			ent		
		5 Fiberglass		RMP (SR)	`	11 other (specify) N/A	
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS		ABS	12 None used (open hole)		
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot 2 Louvered shutter 4 Key punched		6 Wire wrapped			9 Drilled holes		
CODEEN BEDEOD I MICH INTERNAL S		7 Torcl			•	/A	
SCREEN-LERFORMING INTERVA			. to	ft., Fro	· · ·	ſt.	
GRAVEL PACK INTERV	from ALS: from	ft. to		ft., Fro		ft.	
GRAVEL FACK INTERVALS: IFOM from		ft. to ft. to		ft., Fro ft., Fro		በ. ሰ.	
6 GROUT MATERIAL: 1 Neat co		Cement grout		tonite	4 Other	, lt.	
Grout Intervals: From 0 ft. to 26		ft. From	ft. t		ft. From	ft. to ft.	
What is the nearest source of possible contamination:				10 Livest	taali waxa	Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel s	191	15 Oil well/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon			lizer storage 16 (Other (specify below)	
3 Watertight sewer lines 6 Seepa	9 Feedyard	13 Insecticide storage					
Direction from well? North FROM TO LITHOLOGIC LOG			IIow many feet? 10 FROM TO PLUGGING INTERVALS				
			0	26	cement grout	RVALS	
				12	Comone group		
				<u> </u>			
				 			
				<u> </u>			
				1			
			1				
7 CONTRACTOR'S OR LANDOWNER	's CERTIFICATION: Thi	is water well was (1) constructe	d. (2) reconst	ructed, or (3) plugged under r	nv jurisdiction and	
was completed on (mo/day/year) .	02/14/0	01	. and this rec	ord is true to t	the best of my knowledge and	belief. Kansas Water	
Well Contractor's License No	236	This Water Well R	Record was co	ompleted on (r	mo/day/yr)02/1.	9/01	
Under the business name of.从a.	rb werr ~~	Pump serv	rcetu	.C by (sig	nature)	S. Harp	
					Loui C). <i>Σ</i> ιμι <i>γ</i>	