1 LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212 Section Number	T	D N
Sedgwick	NW 1/4	SW 1/4 S	SE 1/4	12	Township Number T 27 S	Range Number
Distance and direction frem nearest town or city stree	·		DE 1/4	12	T 2/ S	R 1E E/W
13th N. & Woodlawn, 1/2 W., 1/4 N. Wichita, Kansas						
WATER WELL OWNER: ASHCOM, Tom						
RR#, ST. ADRESS, BOX#: 1444 Spring Drive  Board of Agriculture, Divivion of Water Resour						ivivsion of Water Resource
CITY, STATE, ZIP CODE: Wichit				Application Number:		
	DEPTH OF COM	PLETED WELL	127	ft. ELE	EVATION:	
AN "X" IN SECTION BOX:	Depth(s) groundwa	ter Encountered	1	ft.	2 ft.	3 ft.
WE	LL'S STATIC WA		<b>3</b> гт.	BELOW LAND SUR	RFACE MEASURED ON mo/day/yr	03/08/2001
NWNE	Pump test		water was		after hours pum	iping gpm
Est.	Yield	01	water was		after hours pum	
	e Hole Diameter	12 in.	to 127	ft.	and in.	to ft.
l l WE	LL WATER TO B 1 Domestic		5 Public wate 6 Oil field wa			njection well Other (Specify below)
stw	2 Irrigation		7 Lawn and g		0 Monitoring well	odici (Specify below)
<b>! !</b>				····	•	10/day/yr sample was
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted  Water Well Disinfected? Yes X No						
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped						
1 Steel 3 RMP (SR)				Other (Specify be	•	
2 PVC 4 ABS		7 Fiberglass	S	DR-26	ı	Threaded
Blank casing Diameter 5 in.	to 24	ft., Dia	in.	to	ft., Dia in.	to ft.
Casing height above land surface 12	in.,	weight 2			Wall thickness or gauge No.	.214
TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)						
(Constability)						
			<b>A</b>	12 None used (open hole) 8 Saw cut 11 None (open hole)		
SCREEN OR PERFORATION OPENING ARE:  1 Continuous slot  3 Mill slot		5 Gauzed wrapped 6 Wire wrapped			9 Drilled holes	
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)						
CORPEN REDEODATION INTERNAL C						
from			to	ft., From		
GRAVEL PACK INTERVALS: from 24			to 127	ft., From ft., From		ft. ft.
		to	ft., From		ft.	
6 GROUT MATERIAL: 1 Neat ceme	nt 2 Ce	ement grout	3 Ber	itonite	4 Other bentonite	hole plug
Grout Intervals: From ft. to		ft. From	ft.		ft. From 4	ft. to 24 ft.
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines		7 Pit privy		10 Livestoc		bandon water well
		8 Sewage lagoon		11 Fuel sto 12 Fertiliz	130	Oil well/Gas well
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit					cide storage 16 (	Other (specify below)
	IOLOGIC LOG		FROM	то	How many feet? 100 PLUGGING INTE	RVALS
0 4 topsoil						
4   10   clay						
10 12 fine sand			<u> </u>			
12   127   shale						
			<b>-</b>			
				<u> </u>	779	
					400	
		711-4-				74.
					7.00	
						7
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)						
was completed on (mo/day/year)	03/08/0	11	and this rec	ord is true to th	e best of my knowledge and	belief. Kansas Water
Well Contractor's License No236						
Todd S. Harp						