

LOCATION OF WATER WELL: County: <u>Sedgwick</u>	Fraction <u>NE 1/4 SE 1/4 NE 1/4</u>	Section Number <u>16</u>	Township Number <u>T 27 S</u>	Range Number <u>R 1 E</u>
--	---	-----------------------------	----------------------------------	------------------------------

Distance and direction from nearest town or city street address of well if located within city?

358' S. of 11<sup>th</sup> ST. N and 1'E of I-135 Wichita, KS NMW-16D


WATER WELL OWNER: City of Wichita

R#, St. Address, Box #: 1900 E. 9<sup>th</sup> STREET  
City, State, ZIP Code: Wichita, KS 67214

Board of Agriculture, Division of Water Resources

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 29 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 14.5 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield N.A. gpm: Well water was ft. after hours pumping gpmBore Hole Diameter 2 1/8 in. to 29 ft., and in. to ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring wellWas a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:

- 1 Steel 3 RMP (SR)  
2 PVC 4 ABS

- 5 Wrought iron 6 Asbestos-Cement  
 7 Fiberglass

- 8 Concrete tile 9 Other (specify below)

CASING JOINTS: Glued Clamped

Welded

Threaded XBlank casing diameter 3/4 in. to 21.9 ft., Dia in. to ft., Dia in. to ft.Casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No. SCH 80

TYPE OF SCREEN OR PERFORATION MATERIAL:

- 1 Steel 3 Stainless steel  
 2 Brass 4 Galvanized steel

- 5 Fiberglass 6 Concrete tile

- 7 PVC 8 RMP (SR)  
 9 ABS

- 10 Asbestos-cement 11 Other (specify)  
 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

- 1 Continuous slot 3 Mill slot  
 2 Louvered shutter 4 Key punched

- 5 Gauzed wrapped 6 Wire wrapped  
 7 Torch cut

- 8 Saw cut 9 Drilled holes  
 10 Other (specify) 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 21.9 ft. to 29 ft., From ft. to ft.GRAVEL PACK INTERVALS: From 19 ft. to 29 ft., From ft. to ft.GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 OtherGrout intervals: From 0 ft. to 19 ft., From ft. to ft.

What is the nearest source of possible contamination:

- 1 Septic tank 4 Lateral lines  
 2 Sewer lines 5 Cess pool  
 3 Watertight sewer lines 6 Seepage pit

- 7 Pit privy 8 Sewage lagoon  
 9 Feedyard

- 10 Livestock pens 14 Abandoned water well  
 11 Fuel storage 15 Oil well/Gas well  
 12 Fertilizer storage 16 Other (specify below)  
 13 Insecticide storage

Location from well?

FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0	16	Sandy Clay			
16	29	Sand			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-16-01 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 604 This Water Well Record was completed on (mo/day/yr) 1-16-01Under the business name of Environmental Priority Service, Inc by (signature) Dave Ray

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send two three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4