

LOCATION OF WATER WELL:
Fraction
Section Number
Township Number
Range Number

County: Sedgwick
NW 1/4 SE 1/4 NE 1/4
17
T 27 S
R 1 BW

Distance and direction from nearest town or city street address of well if located within city?

4' N & 10th St. N. and 75' W. of Main
Wichita, KS
NMW-230

WATER WELL OWNER: City of Wichita
R#, St. Address, Box #: 1900 E. 9th STREET
City, State, ZIP Code: Wichita, KS 67214

Board of Agriculture, Division of Water Resources
Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

DEPTH OF COMPLETED WELL: 39.9 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 14.3 ft. 2. ft. 3. ft.

WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr

Pump test data: Well water was ft. after hours pumping gpm

Est. Yield N/A gpm: Well water was ft. after hours pumping gpm

Bore Hole Diameter 2 1/8 in. to 4 in. to ft. and in. to ft.

WELL WATER TO BE USED AS:
5 Public water supply
8 Air conditioning
11 Injection well
1 Domestic
3 Feedlot
6 Oil field water supply
9 Dewatering
12 Other (Specify below)
2 Irrigation
4 Industrial
7 Lawn and garden only
10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:
1 Steel
3 RMP (SR)
2 PVC
4 ABS

5 Wrought iron
8 Concrete tile
6 Asbestos-Cement
9 Other (specify below)
7 Fiberglass

CASING JOINTS: Glued Clamped Welded Threaded X

casing diameter 3/4 in. to 29.8 ft., Dia in. to ft., Dia in. to ft.

casing height above land surface Flush in., weight lbs./ft. Wall thickness or gauge No SCH 80

TYPE OF SCREEN OR PERFORATION MATERIAL:
1 Steel
3 Stainless steel
5 Fiberglass
8 RMP (SR)
2 Brass
4 Galvanized steel
6 Concrete tile
9 ABS

10 Asbestos-cement
11 Other (specify)
12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:
1 Continuous slot
3 Mill slot
5 Gauzed wrapped
8 Saw cut
11 None (open hole)
2 Louvered shutter
4 Key punched
6 Wire wrapped
9 Drilled holes
7 Torch cut
10 Other (specify)

SCREEN-PERFORATED INTERVALS:
From 29.8 ft. to 39.4 ft.
From ft. to ft.
From ft. to ft.

GRAVEL PACK INTERVALS:
From 23 ft. to 39.9 ft.
From ft. to ft.
From ft. to ft.

GROUT MATERIAL:
1 Neat cement
2 Cement grout
3 Bentonite
4 Other

Grout intervals: From 0 ft. to 23 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:
1 Septic tank
4 Lateral lines
7 Pit privy
10 Livestock pens
14 Abandoned water well
2 Sewer lines
5 Cess pool
8 Sewage lagoon
11 Fuel storage
15 Oil well/Gas well
3 Watertight sewer lines
6 Seepage pit
9 Feedyard
12 Fertilizer storage
16 Other (specify below)
13 Insecticide storage

Direction from well?
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3 Silty Sand
3 40 Sand

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-12-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 604 This Water Well Record was completed on (mo/day/yr) 3-12-01 under the business name of Environmental Priority Service, Inc by (signature)

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.