1 LOCATION OF WATER WELL:	FRACTION	Water Well Re	cord Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
Sedgwick	NW 1/4	NW 1/4	NW 1/4	8	27	157	
Distance and direction frem nearest town or city s			7414		T 2/s	I R IE E/W	
2122 Hood		Wichita,	Vangag				
	, Kathy	MACHALCA	Rambas			**************************************	
	Hood				Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Wich:	18	Application Number:			ver:		
LOCATE WELL'S LOCATION WITH 4		VEL TE WELL	L 35	n. EL	EVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundw			ſt.	2 ft.	3 ft.	
	WELL'S STATIC W	ATER LEVEL	17 FT	. BELOW LAND SU	URFACE MEASURED ON mo/day/yr	04/04/2001	
NWNE	Pump tes		ll water was	ſt.	after hours pur	nping gpm	
<u>u</u> E	st. Yield	.	ell water was	ſt.	after hours pur	nping gpm	
	ore Hole Diameter		to	ft.	and in.	to ft.	
	VELL WATER TO		5 Public wate	•		Injection well	
swsie	1 Domestic 2 Irrigation	3 FeedIot 4 Industrial	6 Oil field wa 7 Lawn and g		9 Dewatering 12 10 Monitoring well	Other (Specify below)	
	z irrigation Vas a chemi <u>c</u> al/bacte				Н	mo/day/yr sample was	
1 6 1	vas a cnemical/bacte submitted	:Hotogical sample	Submitted to De	-		mo/day/yr sampie was X No	
5 TYPE OF CASING USED:	3UDIMET-	5 Wrought iro	8	Concrete tile		Glued Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cer		Other (Specify b	· · · · · · · · · · · · · · · · · · ·		
2 PVC 4 ABS		7 Fiberglass			•	Threaded X	
	n. to	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface 60	,	weight		lbs. / ft.	Wall thickness or gauge No.		
TYPE OF SCREEN OR PERFORATION	e manamana		PVC	10 Asbestos-cem			
1 Steel 3 Stainless Steel	5 Fiberglass		RMP (SR)		11 other (specify) N/A		
2 Brass 4 Galvanized steel	6 Concrete tile		ABS	12 None used (o	•		
SCREEN OR PERFORATION OPEN 1 Continuous slot 3 Mill slot			auzed wrapped		8 Saw cut	11 None (open hole)	
S Will Slot			6 Wire wrapped		9 Drilled holes	-	
· ·			rch cut			T/A	
SCREEN-PERFORATION INTERVAL			ft. to	ft., Fron		ft.	
GRAVEL PACK INTERVA	from ALS: from	ft. to		ft., Fron		ft.	
ORATED I ACK IITI EKTA	from		ft. to	ft., Froi ft., Froi	10. 00	•••	
6 GROUT MATERIAL: 1 Neat cer		Cement grout		ntonite			
Grout Intervals: From 0 ft. to 3		ft. From			4 Other bentonite hole plug ft. From 3 ft. to 35 ft.		
What is the nearest source of possible contamination:				10 Livesto	•	Abandon water well	
1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel st	13	Oil well/Gas well	
2 Sewer lines 5 Cess po		8 Sewage lagoon				Other (specify below)	
3 Watertight sewer lines 6 Secpage	9 Fcedyard		13 тизеси	icide storage None	a Apparent		
Direction from well? Ilow many feet? FROM TO PLUGGING INTERV							
TROM TO LI	THOLOGIC LOG		FROM 0	3 TO	PLUGGING INTE	RVALS	
			3		bentonite hole	plua	
			7			-F3	
					The state of the second of the second		
						····	
				-			
				1			
				11-			
		***************************************		1			
7 CONTRACTOR'S OR LANDOWNER'S	CEPTIFICATION: Th	ie water well wa	e (1) construct	ad (2) reconstr	rusted or (3) plunged under i	iuriediation and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Well Contractor's License No23.6							
Under the business name of Har		TIIIS VVAICE VVEII	Record was c	ombiered on (ii	no/day/yr)	······································	
Onder the pusiness name of www.	p Well &	Pump Ser	viceIr	Simpleted on (in Sigr	nature)	S. Нагр	