				Water Well Record	Form WWC-5	KSA 82a-1212	•	
1 LOCA		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
			SE 1/4	NE 1/4 N	N 1/4	66	T 27 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
2844 N. Charles Wichita, Kansas								
WATER WELL OWNER: MATTHEWS, Jerry RR#, ST. ADRESS, BOX#: 2844 N. Charles Board of Agriculture, Divivsion of Water Resource								
			N. Charle		•			
	, STATE, ZII		hita, Kans		4.0	e Ele	Application Numb	ver:
	' IN SECTIO	OCATION WITH N BOX:		MPLETED WELL vater Encountered	40 1	ft. ELE ft.	VATION: 2 ft.	3 ft.
1 +		N	, .	VATER LEVEL 20	_		RFACE MEASURED ON mo/day/yr	05/18/2001
1			Pump te		iter was		after hours pur	
<u> </u>	NW	X NE	Est. Yield	***************************************	ater was		after hours put	
W Kiji		T.	Bore Hole Diameter	61	o 40	ft.	and in.	- 0
ξw		E	WELL WATER TO		Public water	_		Injection well
1 .		s	1 Domestic	3 Feedlot 6	Oil field wate	er supply	9 Dewatering 12	Other (Specify below)
1	3,4		2 Irrigation	4 Industrial 7	Lawn and ga	rden only 1	0 Monitoring well	
↓			Was a chemical/bact	eriological sample sub	mitted to Dep	partment? Yes	No X; If yes,	mo/day/yr sample was
<u> </u>		S	submitted			Wat	er Well Disinfected? Yes	X No
		SING USED:		5 Wrought iron		Concrete tile		Glued X Clamped
1 Stee		3 RMP (SR)		6 Asbestos-Cement	90	Other (Specify b	•	Welded
2 PVC	_	4 ABS		7 Fiberglass	SI	R-26		Threaded
1	sing Diam	_	in. to 30	ft., Dia	in.	to	ft., Dia in.	to ft.
		ve land surface 1	L 2 in. , TION MATERIAL:	weight 2.		lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-cen	.214
1 Stee		3 Stainless Steel	HON WATERIAL:	5 Fiberglass	_	RMP (SR)	11 other (specif	
2 Brass 4 Galvanized steel 6 Concrete tile						9 ABS 12 None used (open hole)		
						95		
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed 1 Continous slot 3 Mill slot 6 Wire wr						Wiappeu		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREE	N-PERFO	RATION INTERV			o 40	ft., From	`•	ft.
			from	ft. 1		ft., From		
AM W					to 40	ft., From		
			from	ft.		ft., From		
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.								
What is the nearest source of possible contamination:								Abandon water well
1 Septi		4 Later	al lines	7 Pit privy	•			Oil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage l					12 Fertilizer storage 13 Insecticide storage		Other (specify below)	
5 Seepage pit 7 recuyard								
Direction from well? South How many feet? 40								DVALC
0	4	topsoil	LITHOLOGIC LOG		FROM	10	TLUGGING INTI	AVALS
4	18	clay						
18	25	medium s	and					
25	40	coarse s						
ļ								
	<u> </u>						AMERICAN ACCURATE ACCURATION AND ACC	
							.	
ļ						 -		
	1							
			parties and the second				AND THE CONTRACT OF STREET	
			*			<u> </u>	- m8 - 1 - 11 - 12 - 12 - 12 - 12 - 12 - 12	
7 000	ITD ACT	Dig or		hio water well		d (2) ======	usted or /2\ mlummadd-:	my juriodiation and
Huse of	n I KACT(ompleted	on (moldaylysar	CRECERTIFICATION: 11	nis water well was (1 ' 0 1	nd this rece	u, (∠) reconstri ord is true to th	ucted, or (3) plugged under ie best of my knowledge an	my jurisuiction and d helief. Kansas Water
							o/day/yr)0.5./.2	
Under the business name of Harn Well & Pump Service Inc. by (signature)								
1			_	_		•	Lodd	S. Нагр