				Water Well Record	Form WWC-5	KSA 82a-1212		
Ľ		TER WELL:	FRACTION SE		_ 1	Section Number	Township Number	Range Number
			NE 1/4	SW 1/4 NI	€ 1/4	7	T 27 s	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
1849 Woodrow Ave Wichita, Kansas								
WATER WELL OWNER: BLYTHE, Lewis  RR#, ST. ADRESS, BOX #: 1849 Woodson, Ave.  Board of Agriculture, Divivsion of Water Resource								
1019 WOOdlow Ave								
-		OCATION WITH		OMPLETED WELL	40	n. ELE	Application Number	
	IN SECTIO			water Encountered	1	ft.	2 ft.	3 ft.
l t				WATER LEVEL 15			FACE MEASURED ON mo/day/yr	05/22/2001
]		NIE.		est data: Well wa	ter was	ft. a	fter hours pum	
	NW	\_ <b>X</b> E	Est. Yield	gpm: Well wa	ater was		after hours pum	
Mile M		E	Bore Hole Diamete	r 12 in. t	40	ſt.	and in.	to ft.
=			WELL WATER TO		Public water		•	njection well
l i	sw	sec	1 Domestic		Oil field wat		J	Other (Specify below)
			2 Irrigation		Lawn and ga		0 Monitoring well	
+	i_	S		cteriological sample sub	mitted to De	•		o/day/yr sample was
submitted water well disinfected? Yes X No								
1 Steel		3 RMP (SR)		5 Wrought iron 6 Asbestos-Cement	_	Concrete tile Other (Specify be		lued X Clamped
								Threaded
l ——	_		in. to 30	ft., Dia	رم in.	to	ft., Dia in.	to ft.
Blank casing Diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214								
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								)
2 Bras	s	4 Galvanized stee	el	6 Concrete tile	9	ABS	12 None used (or	en hole)
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed w						• • • • • • • • • • • • • • • • • • •		
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 30 ft. to 40 ft., From ft. to								
from ft. to						ft., From	ft. to	ft.
1					to 40	ft., From ft., From		ft. ft.
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plu								
Grout Intervals: From ft. to ft. From ft. to ft. From 4 ft. to 24 ft.								
What is the nearest source of possible contamination:								bandon water well
1 Septic tank 4 Lateral lines 7 Pit privy						11 Fuel storage 15		Dil well/Gas well
2 Sewer lines 5 Cess pool 8 Sewage					n	12 Fertilizer storage		Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction from well? West How many feet? 95								
FROM	TO		LITHOLOGIC LO	3	FROM_	ТО	PLUGGING INTE	RVALS
0 4	<b>4</b> 8	topsoil clay				-		
8	15	fine sar	nd				100	
15	40	coarse s						
							of the second se	
							- A- 45°	
					ļ	<del>                                     </del>		
						-	EAST-PLANT	46-77
						-		
				to the second or the second of				
7 00	ITD 1 CT	NDIC or		This water well was a 44	oor-t	nd (2) no no no to	oted or (2) plugged under	ny juriediation and
1 1 00							icted, or (3) plugged under r e best of my knowledge and	
Well C	ontracto	r's License No	236	This Water Well Re	cord was c	ompleted on (m	o/day/yr)05./.2.	5/01
Under the business name of Harp Well & Pump Service. Inc. by (signature)  Todd S. Harp								
I							Load .	). <i>JUITO</i>