

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: County: SEDGWICK		Fraction SW 1/4 NW 1/4 SW 1/4		Section Number 23	Township Number T 27 S	Range Number R 1 EW
Distance and direction from nearest town or city street address of well if located within city? 248 S. Hillside Wichita, KS. 67214						MW#3
2 WATER WELL OWNER: DIAMOND SHAMROCK RR#, St. Address, Box #: 5590 HAVANA ST City, State, ZIP Code: DENVER, CO 80329				Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION:				
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter: 7 1/4 in. to 32 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped X 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded. X Blank casing diameter 2 in. to 17 ft. Dia in. to ft. Dia in. to ft. Casing height above land surface 0 in., weight sched 40 lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: X7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot X3 Mill slot 010 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 32 7 Torch cut 17 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 32 ft. to 17 ft. From ft. to ft. From 32 ft. to 15 ft. From ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft.				
		6 GROUT MATERIAL: 1 Neat cement X 2 Cement grout 15 X8 Bentonite 12 4 Other Grout Intervals: From 12 ft. to -0.03 ft. From 15 ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy X11 Fuel storage 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage 16 Other (specify below) Direction from well? west How many feet? 20				
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS				
0	12"	ASPHALT				
12"	5	BRN SILTY CLAY				
5	12	BRN SILTY MOTTELED CLAY				
12	18	BRN SILTY SLIGHTLY SANDY CLAY				
18	22	SILTY CLAYEY BRN SAND				
22	28	FINE TO MEDIUM SAND				
		WET AT 27.5				
28	32	MEDIUM TO COARSE SAND				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-13-98 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 575 This Water Well Record was completed on (mo/day/yr) 5-31-98 under the business name of KURTZ ENVIRONMENTAL SERVICE by (signature)						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4