1 LOCATION OF WATER WELL:		FRACTION	water	r well Reco	ord Form W	WC-3	Section Number	Township Number	Range Number	
		am, SE SE	SW		ATT:	1/4				
Sedgwick 9N 1/4  Distance and direction frem nearest town or city street address of well if local				1/4	NE	1/4	6	T 27 s	R 1E E/W	
2614 N. Porter Wichita, Kansas										
WATER WELL OWN	11411	-								
RR#, ST. ADRESS, BOX#: 2614 N. Porter  Board of Agriculture, Divivision of Water Resource										
CITY, STATE, ZIP CODE: Wichita, Kansas							Application Number:			
LOCATE WELL'S LOCA	v. <b>–</b>	DEPTH OF COM				)		VATION:		
A LYBERTON BO	<sup>D</sup>	epth(s) groundwa			1		ft.	2 ft.	3 ft.	
	WEI	LL'S STATIC WA		VEL 1	L5	FT	. BELOW LAND SUR	FACE MEASURED ON mo/day/yr	05/31/2001	
NW	NE	Pump test	data:	Well	water wa	S	ft. a	after hours pum	nping gpm	
ايوا		Yield	gpm:	Wel	l water wa		ft. a	after hours pum	nping gpm	
W Wiji	- LE	Hole Diameter	12	in.	to 4	-	ft.	and in.	to ft.	
	i <b>i i</b>	LL WATER TO B			5 Public			•	injection well	
sw	SE	1 Domestic	3 Feedlo					•	Other (Specify below)	
	i <b>I I</b>	2 Irrigation	4 Indust					0 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was										
submitted water well Districted? Yes X No										
5 TYPE OF CASIN	G USED: 3 RMP (SR)		5 Wrou	_			Concrete tile		Glued X Clamped	
1 Steel					Other (Specify below) Welded					
2 PVC	4 ABS		7 Fiberg	glass		S	DR-26	Т	Threaded	
Blank casing Diameter	•	to 30	ft. ,	Dia		in.	to	ft., Dia in.	to ft.	
Casing height above la		in.,	•	weight	2.35			Wall thickness or gauge No.	.214	
TYPE OF SCREEN C		MATERIAL:	5 Fibergl	logg			PVC	10 Asbestos-cem		
	Stainless Steel		Ū				RMP (SR)	11 other (specify	•	
2 Brass 4 Galvanized steel 6 Concrete tile						9	ABS	12 None used (o)	•	
SCREEN OR PERFORATION OPENING ARE:					5 Gauzed wrapped			8 Saw cut 11 None (open hole)		
1 Continous slot 3 Mill slot 6 Wire wra						l		9 Drilled holes		
2 Louvered shutter	4 Key punche			7 Tor	ch cut			10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 30 ft. to 4							ft., From	ft. to	ſt.	
from			ft. to			ft., From	ft. to	ft.		
GRAVEL PACK INTERVALS: from 24			ft. to 40			ft., From	ft. to	ft.		
from				ft. to			ft., From		ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout						3 Bei	ntonite	4 Other bentonite	hole plug	
Grout Intervals: From ft. to			ft. From			ſŧ.		ft. From 4	ft. to $24$ ft.	
What is the nearest source of possible contamination:  1 Septic tank  4 Lateral lines			7 Die maine				10 Livestoc		Abandon water well	
			7 Pit privy				11 Fuel sto	130	Oil well/Gas well	
2 Sewer lines 5 Cess pool			8 Sewage lagoon 9 Feedyard				12 Fertiliz	er storage 16 ( cide storage	Other (specify below)	
3 Watertight sewer lin	FB- F-	it	9 Fe	edyard			10 11200000			
Direction from well? East FROM TO LITHOLOGIC LOG				FROM TO			1 TO 1	How many feet? 90	DVAVC	
	opsoil	OLOGIC LOG			FRO	JM	TO	PLUGGING INTE	RVALS	
	lay				-				, A. 141.	
	edium sand									
	oarse sand								·	
	CATBE BAIL	<u> </u>								
								Alberto de ve	A	
		74.44								
									described the second se	
		* *************************************								
								LORDER .		
7 CONTRACTORS						-				
CONTRACTORS								icted, or (3) plugged under r		
								e best of my knowledge and		
Well Contractor's License No										
onder the business	VIIIAMM	m						Todd .	S. Harp	