

LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>Sedawick</u>	<u>NE 1/4 SE 1/4 NE 1/4</u>	<u>4</u>	<u>T 27 S</u>	<u>R 1 E/W</u>

stance and direction from nearest town or city street address of well if located within city?
340' W. of New York + 3950' N. of 21st Wichita, KS Nmb-36D

WATER WELL OWNER: City of Wichita
 R#, St. Address, Box # : 1900 E. 9th St.
 ty, State, ZIP Code : Wichita, KS. 67214

Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 4 DEPTH OF COMPLETED WELL... 38 ft. ELEVATION:

Depth(s) Groundwater Encountered	ft 1	ft 2	ft 3	ft
11.15				

N

NW	NE
SW	SE

S

W

E

Depth(s) Groundwater Encountered: 1. 2.0 ft. 2. 3.0 ft. 3. 4.0 ft. 4. 5.0 ft. 5. 6.0 ft. 6. 7.0 ft. 7. 8.0 ft. 8. 9.0 ft. 9. 10.0 ft. 10. 11.0 ft. 11. 12.0 ft. 12. 13.0 ft. 13. 14.0 ft. 14. 15.0 ft. 15. 16.0 ft. 16. 17.0 ft. 17. 18.0 ft. 18. 19.0 ft. 19. 20.0 ft. 20. 21.0 ft. 21. 22.0 ft. 22. 23.0 ft. 23. 24.0 ft. 24. 25.0 ft. 25. 26.0 ft. 26. 27.0 ft. 27. 28.0 ft. 28. 29.0 ft. 29. 30.0 ft. 30. 31.0 ft. 31. 32.0 ft. 32. 33.0 ft. 33. 34.0 ft. 34. 35.0 ft. 35. 36.0 ft. 36. 37.0 ft. 37. 38.0 ft. 38. 39.0 ft. 39. 40.0 ft. 40. 41.0 ft. 41. 42.0 ft. 42. 43.0 ft. 43. 44.0 ft. 44. 45.0 ft. 45. 46.0 ft. 46. 47.0 ft. 47. 48.0 ft. 48. 49.0 ft. 49. 50.0 ft. 50. 51.0 ft. 51. 52.0 ft. 52. 53.0 ft. 53. 54.0 ft. 54. 55.0 ft. 55. 56.0 ft. 56. 57.0 ft. 57. 58.0 ft. 58. 59.0 ft. 59. 60.0 ft. 60. 61.0 ft. 61. 62.0 ft. 62. 63.0 ft. 63. 64.0 ft. 64. 65.0 ft. 65. 66.0 ft. 66. 67.0 ft. 67. 68.0 ft. 68. 69.0 ft. 69. 70.0 ft. 70. 71.0 ft. 71. 72.0 ft. 72. 73.0 ft. 73. 74.0 ft. 74. 75.0 ft. 75. 76.0 ft. 76. 77.0 ft. 77. 78.0 ft. 78. 79.0 ft. 79. 80.0 ft. 80. 81.0 ft. 81. 82.0 ft. 82. 83.0 ft. 83. 84.0 ft. 84. 85.0 ft. 85. 86.0 ft. 86. 87.0 ft. 87. 88.0 ft. 88. 89.0 ft. 89. 90.0 ft. 90. 91.0 ft. 91. 92.0 ft. 92. 93.0 ft. 93. 94.0 ft. 94. 95.0 ft. 95. 96.0 ft. 96. 97.0 ft. 97. 98.0 ft. 98. 99.0 ft. 99. 100.0 ft. 100. 101.0 ft. 101. 102.0 ft. 102. 103.0 ft. 103. 104.0 ft. 104. 105.0 ft. 105. 106.0 ft. 106. 107.0 ft. 107. 108.0 ft. 108. 109.0 ft. 109. 110.0 ft. 110. 111.0 ft. 111. 112.0 ft. 112. 113.0 ft. 113. 114.0 ft. 114. 115.0 ft. 115. 116.0 ft. 116. 117.0 ft. 117. 118.0 ft. 118. 119.0 ft. 119. 120.0 ft. 120. 121.0 ft. 121. 122.0 ft. 122. 123.0 ft. 123. 124.0 ft. 124. 125.0 ft. 125. 126.0 ft. 126. 127.0 ft. 127. 128.0 ft. 128. 129.0 ft. 129. 130.0 ft. 130. 131.0 ft. 131. 132.0 ft. 132. 133.0 ft. 133. 134.0 ft. 134. 135.0 ft. 135. 136.0 ft. 136. 137.0 ft. 137. 138.0 ft. 138. 139.0 ft. 139. 140.0 ft. 140. 141.0 ft. 141. 142.0 ft. 142. 143.0 ft. 143. 144.0 ft. 144. 145.0 ft. 145. 146.0 ft. 146. 147.0 ft. 147. 148.0 ft. 148. 149.0 ft. 149. 150.0 ft. 150. 151.0 ft. 151. 152.0 ft. 152. 153.0 ft. 153. 154.0 ft. 154. 155.0 ft. 155. 156.0 ft. 156. 157.0 ft. 157. 158.0 ft. 158. 159.0 ft. 159. 160.0 ft. 160. 161.0 ft. 161. 162.0 ft. 162. 163.0 ft. 163. 164.0 ft. 164. 165.0 ft. 165. 166.0 ft. 166. 167.0 ft. 167. 168.0 ft. 168. 169.0 ft. 169. 170.0 ft. 170. 171.0 ft. 171. 172.0 ft. 172. 173.0 ft. 173. 174.0 ft. 174. 175.0 ft. 175. 176.0 ft. 176. 177.0 ft. 177. 178.0 ft. 178. 179.0 ft. 179. 180.0 ft. 180. 181.0 ft. 181. 182.0 ft. 182. 183.0 ft. 183. 184.0 ft. 184. 185.0 ft. 185. 186.0 ft. 186. 187.0 ft. 187. 188.0 ft. 188. 189.0 ft. 189. 190.0 ft. 190. 191.0 ft. 191. 192.0 ft. 192. 193.0 ft. 193. 194.0 ft. 194. 195.0 ft. 195. 196.0 ft. 196. 197.0 ft. 197. 198.0 ft. 198. 199.0 ft. 199. 200.0 ft. 200. 201.0 ft. 201. 202.0 ft. 202. 203.0 ft. 203. 204.0 ft. 204. 205.0 ft. 205. 206.0 ft. 206. 207.0 ft. 207. 208.0 ft. 208. 209.0 ft. 209. 210.0 ft. 210. 211.0 ft. 211. 212.0 ft. 212. 213.0 ft. 213. 214.0 ft. 214. 215.0 ft. 215. 216.0 ft. 216. 217.0 ft. 217. 218.0 ft. 218. 219.0 ft. 219. 220.0 ft. 220. 221.0 ft. 221. 222.0 ft. 222. 223.0 ft. 223. 224.0 ft. 224. 225.0 ft. 225. 226.0

TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
② PVC 4 ABS 7 Fiberglass Threaded
Blank casing diameter 3/4 in. to 30.1 ft., Dia in. to ft., Dia in. to ft.
Casing height above land surface Flush in. weight lbs./ft. Wall thickness or gauge No. SCH 80

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel	3 Stainless steel	5 Fiberglass	7 PVC	10 Asbestos-cement
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)	11 Other (specify)
			9 ABS	12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes	
		7 Torch cut	10 Other (specify)	

GREEN-PERFORATED INTERVALS: From 50.1 ft. to 52.9 ft. From ft. to ft.
From ft. to ft. From ft. to ft.
GRAVEL PACK INTERVALS: From 27.9 ft. to 32.6 ft. From ft. to ft.
From ft. to ft. From ft. to ft.

GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other

Grout intervals: From 1 ft. to 27.9 ft. From ft. to ft. From ft. to ft.

What is the nearest source of possible contamination:

1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well?			13 Insecticide storage	
			How many feet?	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	8'	Clay			
8	12	Silty Clay			
12	25	Sand			
25	29	Clay			
29	37	Sand : GRAVEL			
37	-	Shale			

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-6-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 604 This Water Well Record was completed on (mo/day/yr) 7-18-01 under the business name of Environmental Pioneers Service, Inc. by (signature) [Signature]