

LOCATION OF WATER WELL: Fraction NW 1/4 NE 1/4 SE 1/4 Section Number 4 Township Number T 27 S Range Number R 1 E
 County: Sedgwick
 Distance and direction from nearest town or city street address of well if located within city?
20' E. of Cleveland + 2100' N. of 21st, Wichita, KS. NMW-425
 WATER WELL OWNER: City of Wichita
 #, St. Address, Box #: 1900 E. 9th St
 City, State, ZIP Code: Wichita, KS, 67214
 Board of Agriculture, Division of Water Resources
 Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

NW	NE
SW	SE

W E

4 DEPTH OF COMPLETED WELL: 19.0 ft. ELEVATION: 12.4 ft.
 Depth(s) Groundwater Encountered 1. 12.4 ft. 2. 12.4 ft. 3. 12.4 ft.
 WELL'S STATIC WATER LEVEL: NA ft. below land surface measured on mo/day/yr
 Pump test data: Well water was 19.0 ft. after 19.0 hours pumping 19.0 gpm
 Est. Yield 19.0 gpm; Well water was 19.0 ft. after 19.0 hours pumping 19.0 gpm
 Bore Hole Diameter: 2 1/8 in. to 19.0 ft., and 19.0 in. to 19.0 ft.
 WELL WATER TO BE USED AS:
 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No X

TYPE OF BLANK CASING USED:

5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded Threaded
2 PVC 4 ABS 7 Fiberglass

Blank casing diameter: 3 1/4 in. to 9.1 ft., Dia. 9.1 in. to 9.1 ft., Dia. 9.1 in. to 9.1 ft.
 Casing height above land surface: 40 in., weight 40 lbs./ft. Wall thickness or gauge No. 50

TYPE OF SCREEN OR PERFORATION MATERIAL:

7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE:

5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 9.1 ft. to 18.9 ft., From 9.1 ft. to 18.9 ft., From 9.1 ft. to 18.9 ft.

GRAVEL PACK INTERVALS: From 7.3 ft. to 19.0 ft., From 7.3 ft. to 19.0 ft., From 7.3 ft. to 19.0 ft.

GROUT MATERIAL:

1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout intervals: From 7.3 ft. to 7.3 ft., From 7.3 ft. to 7.3 ft., From 7.3 ft. to 7.3 ft.

What is the nearest source of possible contamination:

1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
		<u>NA</u>			
<u>0</u>	<u>11</u>	<u>Clay</u>			
<u>11</u>	<u>16</u>	<u>Silt Clay</u>			
<u>16</u>	<u>19</u>	<u>Sand</u>			

RECEIVED RECEIVED

OCT 10 2001

AUG 24 2001

BUREAU OF WATER BUREAU OF WATER

CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-5-01 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 604. This Water Well Record was completed on (mo/day/yr) 7-18-01 under the business name of Environmental Priority Service, INC by (signature) [Signature]