110	55.	WAI	ER WELL REC	ORD Form WWC	-5 KSA	82a-1212 IE	No. A-2				
1 LOCATION	OF WA	TER WELL:	Fraction			ction Number		ship Number	Range Num		
County: Sec	dgwick		1/4	SW 1/4 NE	1/4	32	ļτ	27 s	R 1	(E) W	
		from nearest to	wn or city street	address of well if loca	ated within o	ity?	4.00				
		ersection of Skinn									
2 WATER W	ELL OW	NER: City of Wid	1. i							-	
RR#. St. Add	ress. Box	City of Wid # : 455 N. Ma	in				Board	of Agriculture, D	ivision of Water	Resources	
City, State, ZI		· Wichita, K						ation Number:	aviolon of vvalor		
		CATION WITH 4		OMPLETED WELL	37.5	ft FLE\	/ATION: unkn		-		
AN "X" IN		N BOV. H	_	dwater Encountered			ft. 2	ft. 3			
-	N									· · · · · · ·	
1 1	¦	WELL'S STATIC WATER LEVEL not checked ft. below land surface measured on mo/day/yr Pump test data: Well water was not checked ft. after hours pumping gpm									
	NW NE Est. Yield unknown gpm: Well water wasft. after hours pumping gpm										
	!	! ! !	Est. Yield I Turr	ter 18 in. t	erwas 31	π 7.5	. atter	nours p	tumping	gpm	
∰ w	<u> </u>	E '								R.	
7						Public water supply 8 Air conditioning 11 Injection well					
	w – – l -	SE	1 Domestic	3 Feedlot 6	Oil field wate	r supply	9 Dewaterin	.g 1:	2 Other (specify b)	elow)	
1 1	1	1	2 Irrigation	4 Industrial 7	Domestic (la	wn & garden)	10 Monitoring	j well	Extraction We	ell	
<u> </u>	1	<u> </u>	Nas a chemical/ba	acteriological sample s	ubmitted to D	epartment? Yo	es No	√ If yes, m	o/day/yrs sample	e was sub-	
	S		mitted					ected? Yes	,		
5 TYPE OF E	BLANK C	ASING USED:		5 Wrought iron	8 Concr	ete tile	CASIN	NG JOINTS: Glue	d Clampe	d	
1 Steel		3 RMP (SR)	(3 Asbestos-Cement	9 Other	(specify below))	Weld	ed	,	
② _{PVC}		4 ABS	7	7 Fiberglass	-			Threa	aded У	, 	
Blank casing	diamete	r 10 3/4	in. to 20	.5 ft., Dia	i	n. to	ft., D	ia	in. to	ft	
Casing heigh	nt above	and surface	12 in	., weight	12.23	lb	s./ft. Wall thick	ness or gauge N	o .593		
TYPE OF S	CREEN	OR PERFORATI			7 PVC			Asbestos-cemen		·	
1 Steel	ONLEN	3 Stainless st		5 Fiberglass	8 RMP	SB)					
2 Brass		4 Galvanized		6 Concrete tile	9 ABS	Jit,		2 None used (oper			
	R PERF	RATION OPENI		5 Gauzed wr			8 Saw cu		None (open hole)		
1)Continu			ill slot		• •				None (open note)		
_				6 Wire wrapp	ea		9 Drilled			ft.	
2 Least of a state of the state											
SCREE	N-PERFOR	RIED INTERVALS:	From	20.5 ft. to	36.5	ft., Fro		ft. to			
	GRAVEI	PACK INTERVALS		ft. to ft. to	37.5	ft., Fro ft., Fro		ft. to ft. to		- · · · ·	
	OIVAVEE	TAON INTERVALS	From	ft. to	37.5	ft., Fro		ft. to		ft.	
61 00000											
6 GROUT	MATERI	AL: 1 Neat ce	ement 2 Cemer	nt grout 3 Benton		4	Other Bent	onite Holeplug			
Soil Grout Intervals: From 3.5 ft. to 16.5 ft., From 0 ft. to 3.5 ft., From 16.5 ft. to 18.5										ft.	
What is the nearest source of possible contamination:						10 Livestock pens 14 Abandoned water well					
1 Septic tank 4 Lateral lines 7 Pit privy						11 Fuel storage 15 Oil well/Gas well					
						-					
2 Sewer lines 5 Cess pool 8 Sewage lagoo 3 Watertight sewer lines 6 Seepage pit 9 Feedyard											
										• • • • • •	
Direction from				How many feet?							
FROM	то	LI	THOLOGIC LOC	3	FROM	то		PLUGGING IN	TERVALS		
0	2	Topsoil									
2	5	Clay, brown									
5	12	Clay, tan									
12	37	Sand and grave	el, fine, medium,	loose, clean	:						
37	37.5	Shale, gray									
			-								
		1.				 					
7	i					1			 		
CONTRACT	OR'S OR	LANDOWNER'S CE	RTIFICATION: Th	nis water well was (1) o	constructed)	(2) reconst	ructed, or (3) plugged und	der my jurisdiction a	nd was	
completed on				9/5/01		and this rec	ord is true to th	ne best of my kno	wledge and belie	f. Kansas	
Water Well Co			185		ell Record w	as completed	d on (mo/day/y	r)	9/26/01/		
under the busi	iness nar	ne of Clarke Wel	l & Equipment, I	nc.		b	y (signature)	Chul W	(lub		
INSTRUCTIONS	S: Use typev	riter or ball point pen. E	LEASE PRESS FIRML	<u>.Y</u> and <u>PRINT</u> clearly. Please 5-296-5524. Send one to WA						Health and	