LOCATION OF WATER WELL:	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212			
Sedgwick		SE 1/4 NW	,	Section Number	Township Number	Range Number	
	1		1/4	13	T 21 S	R 1B E/W	
Distance and direction frem nearest town or city street address of well if located within city?  1812 W. 2nd Wichita, Kansas							
WATER WELL OWNER: APEX ENGINEERING							
RR#, ST. ADRESS, BOX #: 1812 W. 2nd  Board of Agriculture, Division of Water Resource							
	ita, Kansas				Application Numbe		
LOCATE WELL'S LOCATION WITH	4 DEPTH OF PUM	3354 D WELL	40	ft. EI	EVATION:		
AN "X" IN SECTION BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	WELL'S STATIC W	ATER LEVEL 17	FT.	BELOW LAND S	URFACE MEASURED ON mo/day/yr	11-5-2001	
NW NE	Pump test	data: Well w	ater was	ft.	after hours pum	iping gpm	
	Est. Yield	01	ater was	ft.	after hours pum	ping gpm	
E	Bore Hole Diameter	in. t	0	ft.	and in.	to ft.	
-	WELL WATER 164	BE USED AS: 51	Public water			njection well	
	1 Domestic		Oil field wa		ū	Other (Specify below)	
	2 Irrigation		Lawn and g	•	10 Monitoring well		
	Was a chemical/bacte	eriological sample sul	bmitted to D			no/day/yr sample was	
submitted water weit Districted: Yes X No							
1 Steel 3 RMP (SR)	5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 6 Asbestos-Cement 9 Other (Specify below) Welded						
2 PVC 4 ABS		7 Fiberglass	•	yrene	•	veiueu Threaded	
Blank casing Diameter	in. to	ft., Dia 5	in.	to			
Casing height above land surface 3		weight	1111.	lbs. / ft.	ft. , Dia in. Wall thickness or gauge No.	to ft.	
TYPE OF SCREEN OR PERFORA	weight	7	PVC	10 Asbestos-cem	ent		
1 Steel 3 Stainless Steel	5 Fiberglass						
2 Brass 4 Galvanized steel		6 Concrete tile 9 ABS 12 Non		12 None used (o)	•		
SCREEN OR PERFORATION OPENING ARE:		5 Gauzed wrapped 8 Saw cut		8 Saw cut	11 None (open hole)		
1 Continous slot 3 Mill slot		6 Wire v	6 Wire wrapped 9 Drilled holes				
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) N/A						'A	
SCREEN-PERFORATION INTERV	/ALS: from	ft. t	0	ft., Fro	m ft. to	ft.	
from		ft. t	to	ft., Fro		ft.	
GRAVEL PACK INTERVALS: from		ft.	to	ft., Fro		ft.	
from		ft. 1	to	ft., Fro		ft.	
6 GROUT MATERIAL: 1 Neat	cement 2 C	ement grout	3 Ben	tonite	4 Other bentonite h	nole plug	
Grout Intervals: From ft. to ft. From				ft. to ft. From 3 ft. to 23 ft.			
What is the nearest source of possible contamination:  1 Septic tank 4 Lateral lines		7 Dit muiser	7 Dia		bandon water well		
		7 Pit privy 11 Fuel s		15 Oil Well/Gas Well			
2 Sewer lines 5 Cess pool 3 Watertight sewer lines 6 Seepage pit		8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below 13 Insecticide storage None Apparent					
3 Watertight sewer lines 6 Seepa Direction from well?	9 Feedyard	None Apparent					
FROM TO LITHOLOGIC LOG			FROM	то	How many feet? PLUGGING INTE	DVAIC	
			0	3	compacted topsoils		
			3	23	bentonite hole plu		
			23	40	chlorinated sand &	gravel	
				<b>_</b>			
				<del> </del>			
			<b>.</b>	-			
				<del>                                     </del>			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. This water well use (1) constructed (2) reconstructed or (2) plugged under my jurisdiction and							
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)							
Water Well Contractor's License No							
(mo/day/yr) 11-7-2001							
Under the business name of Harp Well & Pump Service, Inc by (signature) Todd S. Harp							