	 .			Water Well R	Record Form WWC-		•	
1 Loc.		ATER WELL:	FRACTION			Section Number	Township Number	Range Number
Sedgwick			SW 1/	4 SE 1/4	SE 1/4	7	T 27 S	R 1E E/W
Distance and direction frem nearest town or city street address of well if located within city?								
1402 Woodrow Wichita, Kansas								
WATER WELL OWNER: WILCOX, Shelby								
RR#, ST. ADRESS, BOX #: 1402 Woodrow Board of Agriculture, Divivsion of Water Resource								
CITY, STATE, ZIP CODE: Wichita, Kansas Application Number							ber:	
	TE WELL'S	LOCATION WITH		COMPLETED WEI			VATION:	
AN	IN SECTIO	N BOX:	,,	ndwater Encounter		ft.	2 ft.	3 ft.
1 [WELL'S STATI	C WATER LEVEL	, 20 FT	BELOW LAND SU	RFACE MEASURED ON mo/day/yr	2-6-2002
	NW-	NE	Pump	test data: W	ell water was	ft.	after hours pu	ımping gpm
و	1		Est. Yield	O .	ell water was	ft.	after hours pu	ımping gpm
1 Mile	v 	E	Bore Hole Diame	ter 12 _{in.}	. to 43	ft.	and in	
-			WELL WATER	TO BE USED AS:	5 Public water		•	Injection well
l ı	-sw-		1 Domestic	3 Feedlot	6 Oil field wa		· ·	Other (Specify below)
11			2 Irrigation	4 Industrial	7 Lawn and	garden only 1	0 Monitoring well	
+	Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample w							
S submitted Water Well Disinfected? Yes X No								
\vdash		ASING USED:		5 Wrought in		Concrete tile	CASING JOINTS:	Glued X Clamped
1 Ste	el	3 RMP (SR)		6 Asbestos-Co	-	Other (Specify b	elow)	Welded
2 PV	<u>C</u>	4 ABS		7 Fiberglass	S	DR-26		Threaded
	asing Diar		in. to 28	ft., Dia	•	to	ft., Dia in.	to ft.
		ve land surface 1		n., weigh	_{ht} 2.35	lbs. / ft.	Wall thickness or gauge No.	
			ATION MATERIA	L: 5 Fiberglass		PVC	10 Asbestos-ce	
1 Ste		3 Stainless Steel	_			RMP (SR)	11 other (spec	• *
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								` • ′
		RFORATION OP			Sauzed wrapped		8 Saw cut	11 None (open hole)
1 Continous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes								
2 Louv	ered shutte	er 4 Key p	unched	7 T	orch cut		10 Other (specify)	
SCREEN-PERFORATION INTERVALS: from 28 ft. to 43 ft., From ft. to ft.								
			from		ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS: from 24				24	ft. to 43 ft., From		ı ft. t	o ft.
from ft. to ft., From ft. to								
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals: From 4 ft. to 2				ft. From ft. to			ft. From	ft. to ft.
What is the nearest source of possible confidence of the source of the source of possible confidence of the source of the						10 Livesto	•	Abandon water well
						11 Fuel ste	1,	Oil well/Gas well
12 Inscaticida storago							Other (specify below)	
3 water ught sewer lines 6 Seepage pit 9 Feeuyaru								
Direction from well? East How many feet? 80 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								PD3/AY C
0	4	topsoil	LITHOLOGIC L	<u> </u>	FROM	1 10	PLUGGING INT	ERVALS
4	18	clay						- 48 - 14 - 4 - 4
18	25	medium sa	nd					
25	30	clay						
30	43	coarse sa	nd					
		77. N. S.						
							The state of the s	
							T B - T 1 (T 2)	
						1		
		,				1	M-New 2017 - 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
							•	A MANAGEMENT AND A STORY
	ŀ						, =	
	ŀ	!				1 1		
7 00	NUTE A COMM	ODIC · · · ·		This		-4	humatad au (2)	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Water Well Contractor's License No								
I 0 0 0000								
(mo/day/yr)2-8-2002 Under the business name of Harp Well & Pump Service, Inc								
Under the business name of								