· ·			T	Water Well Recor	rd Form WWC-5		•		
LOCATION OF WATER WELL: FRACTION			******** 1		Section Number	Township Number	Range Number		
Sedgwick NW 1/4				NW 1/4	12	T 27 S	R 1E E/W		
Distance and direction from nearest town or city street address of well if located within city? 4921 E. 21st St. N. Wichita, Kansas									
	TER WELL		D & LICHLIT		CHILA, K	Insas			
	ST. ADRESS	FOUUMA	. 21st St.				Board of Agriculture	e, Divivsion of Water Resource	
1	Y, STATE, ZII		a, Kansas		Application Number:				
LOCA	TE WELL'S I	LOCATION WITH 4	DEPTH OF COM	APLETED WELL	120	ft. ELE	EVATION:		
MAN "X	" IN SECTIO	ON BOX:	Depth(s) groundw		1	ft.	2 ft.	3 ft.	
	R	w	ELL'S STATIC W	ATER LEVEL 2	5 FT.	BELOW LAND SU	RFACE MEASURED ON mo/day/yi	8-12-2002	
	NW-		Pump test	t data: Well	water was	ft.	after hours p	umping gpm	
ا			t. Yield	OI .	water was	ft.	after hours p	umping gpm	
M M	/		re Hole Diameter	12 in.	to 120	ft.	and in		
-			ELL WATER TO		5 Public wate			1 Injection well	
1	-sw-		1 Domestic	3 Feedlot 4 Industrial	6 Oil field wa	•		2 Other (Specify below)	
			2 Irrigation		7 Lawn and g	•	10 Monitoring well		
*		e 1	as a chemical/bact ubmitted	eriological sample :	submitted to 1	-		, mo/day/yr sample was	
5 TY	PE OF CA	ASING USED:	1Dinitteu	5 Wasasht ivon		Concrete tile	CASING JOINTS:	s X No Glued X Clamped	
1 Stee		3 RMP (SR)		5 Wrought iron 6 Asbestos-Ceme	_	Other (Specify b		Glued A Clamped Welded	
2 PVC		4 ABS		7 Fiberglass	-	DR-26	Cluw)	Threaded	
l ——	asing Dian		. to 25	ft., Dia	in.	to	ft., Dia in.		
	_	ove land surface 12	in.,	weight 2			Wall thickness or gauge No.		
	-	EN OR PERFORATIO	,	5		PYC	10 Asbestos-ce		
1 Stee	el	3 Stainless Steel		5 Fiberglass	8	RMP (SR)	11 other (spec	ify)	
2 Bra	.ss	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used	(open hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped							8 Saw cut	11 None (open hole)	
	inous slot	3 Mill slot		6 Wire	e wrapped		9 Drilled holes		
	ered shutte			7 Torc			10 Other (specify)		
SCREE	N-PERFO	PRATION INTERVAL	LS: from 25	ft	i. to 120	ft., From	ft. t	o ft.	
			from		t. to	ft., From	ı ft. to	o ft.	
GRAVEL PACK INTERVALS: from 24					t. to 120	ft., From		10.	
CPC	TYPE BAAT	TDIAL 1 Neat com	from		t. to	ft., From		· · · · · · · · · · · · · · · · · · ·	
		ERIAL: 1 Neat cem	t. to 24	ement grout		ıtonite	4 Other bentonite		
Grout Intervals: From 4 ft. to 24 ft. From What is the nearest source of possible contamination:					ft. 1	to 10 Livesto	ft. From	ft. to ft.	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel storage		Abandon water well	
2 Sewer lines 5 Cess pool				8 Sewage lag	oon			5 Oil well/Gas well 6 Other (specify below)	
1	ertight sew	•		9 Feedyard		13 Insecticide storage			
Direction from well? North How many feet? 100									
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								ERVALS	
0	3	topsoil							
3	10	fine sand				 			
10	120	grey shale				 	. ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	 		·····		_	-			
						1			
						+ +	NEW COLUMN TO THE PARTY OF THE		
								V-101	
	igsquare								
	 								
	\longmapsto			_					
<u> </u>									
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and									
was completed on (mo/day/year)									
Water Well Contractor's License No									
(Mo/u	(mo/day/yr)8-14-2002 Under the business name of Harp Well & Pump Service, Inc								
Under	the bush	ness name of	.			Dy (3	signature) Okac	a. O. O larg	