

1 LOCATION OF WATER WELL:		Fraction		Section Number	Township Number	Range Number																														
County: Sedgwick		SE ¼ SE ¼ SW ¼	26	T 27 S	R 1 E	(EW)																														
Distance and direction from nearest town or city street address of well if located within city? 3938 East Harry Street, Wichita, Kansas MW-8																																				
2 WATER WELL OWNER: BFS Retail and Commercial Operations, LLC																																				
RR#, St. Address, Box #: 333 East Lake Street				Board of Agriculture, Division of Water Resources																																
City, State, ZIP Code: Bloomingdale, IL 60108				Application Number:																																
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 33.7 ft. ELEVATION: 1340.32 TOC																																		
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.																																		
		WELL'S STATIC WATER LEVEL Dry ft. below land surface measured on mo/day/yr 03/28/02																																		
		Pump test data: Well water was ft. after hours pumping gpm																																		
		Est. Yield gpm: Well water was ft. after hours pumping gpm																																		
		Bore Hole Diameter. 8 in. to 34 ft., and in. to ft.																																		
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well																																				
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted																																				
Water Well Disinfected? Yes No X																																				
5 TYPE OF BLANK CASING USED:																																				
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 2 in. to 19 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface -0.25 in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 Fiberglass 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 19 ft. to 34 ft., From ft. to ft. From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 17 ft. to 34 ft., From ft. to ft. From ft. to ft., From ft. to ft.																																				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other																																				
Grout Intervals: From 1.5 ft. to 17 ft., From ft. to ft., From ft. to ft.																																				
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Former UST Basin Direction from well? North How many feet? 40																																				
<table border="1" style="width:100%; border-collapse: collapse;"> <thead> <tr> <th>FROM</th> <th>TO</th> <th>LITHOLOGIC LOG</th> <th>FROM</th> <th>TO</th> <th>PLUGGING INTERVALS</th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.5</td> <td>Asphalt</td> <td></td> <td></td> <td></td> </tr> <tr> <td>0.5</td> <td>3</td> <td>Fill: Clay, Olive Green to Red Brown</td> <td></td> <td></td> <td></td> </tr> <tr> <td>3</td> <td>12</td> <td>Silty Clay: Dark Brown, Trace of Sand at 10-12 Feet</td> <td></td> <td></td> <td></td> </tr> <tr> <td>12</td> <td>34</td> <td>Clay: Gray/Red-Brown to Olive Green, Calcareous below 25 Feet</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>							FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	0	0.5	Asphalt				0.5	3	Fill: Clay, Olive Green to Red Brown				3	12	Silty Clay: Dark Brown, Trace of Sand at 10-12 Feet				12	34	Clay: Gray/Red-Brown to Olive Green, Calcareous below 25 Feet			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS																															
0	0.5	Asphalt																																		
0.5	3	Fill: Clay, Olive Green to Red Brown																																		
3	12	Silty Clay: Dark Brown, Trace of Sand at 10-12 Feet																																		
12	34	Clay: Gray/Red-Brown to Olive Green, Calcareous below 25 Feet																																		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 03/28/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 416 This Water Well Record was completed on (mo/day/yr) 05/29/02 : by signature [Signature]																																				
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.																																				