Troc	ATTON OF I	A TONS IVINY	ED + CTION	Water Well Reco	rd Form WWC-5	KSA 82a-1212			
سالا	ATION OF W Sedgw	ATER WELL:	FRACTION NW 1/4	NW 1/4	NW 1/4	Section Number 18	Township Number	Range Number	
Distance and direction frem nearest town or city street address of well if lo				1/4	10	T 4 / S	R IE E/W		
1316 N. Arrowhead Wichita, Kansas									
WATER WELL OWNER: MORTON, Joann									
RR#	, ST. ADRESS		N. Arrowhead	l			Board of Agriculture,	Divivsion of Water Resource	
CIT	Y, STATE, ZI	PCODE: Wich:	ita, Kansas	Application Number:					
	ATE WELL'S K" IN SECTIO	LOCATION WITH	4 DEPTH OF COM		40		VATION:		
AN	M SECTION	N BOX:	Depth(s) groundwa		1	ft.	2 ft.	3 ft.	
	^	. J	WELL'S STATIC W			BELOW LAND SUR	FACE MEASURED ON mo/day/yr	5-14-2002	
'	-NW-	NE	Pump test	, . 	water was		ifter hours pur		
1 Wile	1	1 1 1	Est. Yield Bore Hole Diameter	gpm: Well 12 in.	water was		after hours pur		
ΞV	V		WELL WATER TO 1		5 Public water	ft. r sunnly 8	and in. S Air conditioning 11	to ft. Injection well	
١,	L		1 Domestic	3 Feedlot	6 Oil field wa			Other (Specify below)	
	sw-		2 Irrigation	4 Industrial	7 Lawn and g) Monitoring well		
			Was a chemical/bacte	eriological sample	submitted to D	epartment? Yes	No X; If yes,	mo/day/yr sample was	
<u></u>		S	submitted			Wate	er Well Disinfected? Yes	X No	
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
1 Ste		3 RMP (SR)		6 Asbestos-Ceme		Other (Specify be	· ·	Welded	
2 PV		4 ABS		7 Fiberglass	SI	R-26	•	Threaded	
	asing Diar		in. to 30	ft., Dia	in.		ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No21 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								. 214 nent	
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)								• •	
SCREI	EN OR PE	RFORATION OPE	NING ARE:	5 Gauzed wrapped			8 Saw cut	11 None (open hole)	
1 Cont	inous slot	3 Mill slo	ot		e wrapped		9 Drilled holes		
	ered shutte	F		7 Torc	h cut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 30 ft. to 40 ft., From ft. to								ft.	
from				ft. to		ft., From	ft. to	ft.	
GRAVEL PACK INTERVALS: from 24				fi	ft. to 40 ft., From		ft. to	ft.	
from ft. to ft., From ft. to GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole no								ft.	
Grout Intervals: From 4 & to 24									
What is the nearest source of possible contamination:				ft. From ft. to 10 Liv		o 10 Livestoc	ft. From k pens 14.	ft. to ft. Abandon water well	
1 Septic tank 4 Lateral lines				7 Pit privy		11 Fuel stor		15 Oil well/Gas well	
2 Sewer lines 5 Cess pool			pool	8 Sewage lagoon		12 Fertilize	er storage 16	Other (specify below)	
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? East How many feet? 75									
FROM 0	3	topsoil	ITHOLOGIC LOG		FROM	TO	PLUGGING INTE	RVALS	
3	20	fine sand				·			
20	40	coarse san	ıd					7-4	
				T-01					
		7 PP + 4	- 10 (10 to 10 to				and the state of t		
									
		7 80	- DAMPHELIALA						
7 00	NTP ACT	DDIS on the second	DIO OPPERATOR TEL	ie weter well we	/4\ conct	tod (2) massmati	mated or /9\ minerald	or mus jurgicalistics and	
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)									
Water Well Contractor's License No									
(mo/day/yr)5-15-2002									
Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp									