1 LOCATION OF WATER WELL:		FRACTION	Water Well Reco	rd Form WWC-	Section Number	T =v .	1 n v v v	
Sedgwick			SW 1/4	NE 1/4	7	Township Number	Range Number	
SEGGWICK SE 1/4 Distance and direction from nearest town or city street address of well if locate				NE 1/4	/	T 27 S	R IE E/W	
WATER WELL OWNER: BURKE, Harris RR#, ST. ADRESS, BOX #: 1805 W. 18th N. Board of Agriculture, Division of Water Resource								
Wighite Vange								
			ADI ETED WELL	Application Number: TED WELL 40 ft. ELEVATION:				
AN "X" IN SEC		DEPTH OF COM	MPLETED WELL		ft. ELE		2 6	
t r		, .	VATER LEVEL 1	1 5 et		2 ft. RFACE MEASURED ON mo/day/vr	3 ft. 9-9-2002	
	W	Pump tes						
N1		t. Yield		water was		after hours pum		
ž w	X = X	re Hole Diameter	gpm: Well 12 in.	to 40	ft. a ft.	after hours pum		
Σw	1 12	ELL WATER TO	****	5 Public water		and in. B Air conditioning 11 I	to ft. njection well	
		1 Domestic	3 Feedlot	6 Oil field w		· ·	Other (Specify below)	
S	v s.e	2 Irrigation	4 Industrial	7 Lawn and		0 Monitoring well	(epting selen)	
	w	· ·	eriological sample			_	10/day/yr sample was	
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No								
5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped								
1 Steel	3 RMP (SR)		6 Asbestos-Cem		Other (Specify be		Velded	
2 PVC	4 ABS		7 Fiberglass		DR-26	,	hreaded	
Blank casing D	iameter 5 in	. to 25	ft., Dia	in.	to	ft., Dia in.	to ft.	
_	bove land surface 12	in	weight 2			Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement								
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)								
2 Brass	4 Galvanized steel		6 Concrete tile	9	ABS	12 None used (o)	en hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gaustine 5 Gaustin					i wrapped 8 Saw cut 11 None (open hole)			
1 Continous slo	ot 3 Mill slot		6 Wir	e wrapped		9 Drilled holes		
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)								
SCREEN-PERFORATION INTERVALS: from 25 ft. to 40 ft., From ft. to ft.								
		from	ft	t. to	ft., From		ft.	
GRAVEL PACK INTERVALS: from 24			ft. to 40 ft., From			ft.		
<u> </u>		from	f	t. to	ft., From	ft. to	ft.	
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug								
Grout Intervals		t. to 24	ft. From	ft.		ft. From	ft. to ft.	
What is the nearest source of possible contamination:				10 Livestoc		bandon water well		
1 Septic tank 4 Lateral lines			7 Pit privy		11 Fuel sto	130	Dil well/Gas well	
2 Sewer lines 5 Cess pool			12.1			ertilizer storage 16 Other (specify below) secticide storage		
3 water ugitt sever lines o Seepage pit 7 Feeuward								
Direction from well? South How many feet? 75 FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS								
0 4	topsoil	HOLOGIC LOG		FROM	ТО	PLUGGING INTE	RVALS	
4 20	fine sand							
20 40	medium coar	se sand						
			· · · · · · · · · · · · · · · · · · ·					
			//					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION. This water well was (1) constructed (2) reconstructed or (3) plugged under my jurisdiction and								
CONTRACTOR'S or Landowner's Certification: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year)								
Water Well Contractor's License No								
	(mo/day/yr)9-11-2002							
Under the business name of Harp Well & Pump Service, Inc by (signature) Jedd S. Harp								