

017055

1 LOCATION OF WATER WELL: County: Sedgwick Fraction: NW 1/4 NW 1/4 NW 1/4 Section Number: 33 Township Number: T 27 S Range Number: R 1 E

Distance and direction from nearest town or city street address of well if located within city? NW of Osie & Topeka

2 WATER WELL OWNER: RR#, St. Address, Box #: City of Wichita Board of Agriculture, Division of Water Resources  
City, State, ZIP Code: 1900 E 9th St. Wichita KS 67 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 37.5 ft. ELEVATION: 17.5 ft.

Depth(s) Groundwater Encountered 1. 17.5 ft. 2. 17.5 ft. 3. 17.5 ft.

WELL'S STATIC WATER LEVEL 17.5 ft. below land surface measured on mo/day/yr

Pump test data: Well water was 17.5 ft. after 17.5 hours pumping 17.5 gpm

Est. Yield 17.5 gpm: Well water was 17.5 ft. after 17.5 hours pumping 17.5 gpm

Bore Hole Diameter 37.5 in. to 37.5 ft., and 37.5 in. to 37.5 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well  
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)  
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well

Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted

Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped  
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Flush  
Blank casing diameter 16.5 in. to 16.5 ft., Dia 16.5 in. to 16.5 ft., Dia 16.5 in. to 16.5 ft.  
Casing height above land surface flush in., weight 16.5 lbs./ft. Wall thickness or gauge No. Sch

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement  
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 7 PVC 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)  
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 16.5 ft. to 36.5 ft. From 16.5 ft. to 36.5 ft. From 16.5 ft. to 36.5 ft.

GRAVEL PACK INTERVALS: From 15.5 ft. to 37.5 ft. From 15.5 ft. to 37.5 ft. From 15.5 ft. to 37.5 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Concrete  
Grout Intervals: From 0 ft. to 1 ft. From 1 ft. to 15.5 ft. From 1 ft. to 15.5 ft.

What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well  
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well  
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)  
13 Insecticide storage

Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS

0 3.5 Clay

3.5 8.5 Silty clay

8.5 15 Sand w/ silt

15 36.5 Sand

36.5 37.5 Clay, weathered shale

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3/3/02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 4/3/02 under the business name of Geotechnical Services, Inc. by (signature) Allison M. Smith

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.