				WATER WI	ELL RECO	RD For	m WWC-5	KSA 82		0. 0031353		AL
	ION OF WATE		Fraction SW	., c	W 1/4	NE		tion Numb: 28	er Town T	iship Number 27 S	Ran	ge Number 1 (E/)W
		m nearest tow		/-			1/4 ithin city?	20		21 3	K	
	1002 E. Lin						a in ony :					
2 WATER		ER:	Tom Ma				,					,
	ddress, Box #		803 5 th S	Street					Board of	of Agriculture, D	vision of Wa	ater Resources
	ZIP Code		Orange	City, IA	51041				Applica	tion Number:		
2 LOCAT	E WELL'S LO	CATON WITH		, .						10	02 00 TO	
AN "X" I	IN SECTION E	BOX:	DEPTH	OF COMP	PLETED W	ELL	. 23		EVATION:	12	92.00 10	
	N	1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 - 1999 -	Depth(s) Gr	oundwate	r Encounte	ered 1	10	.4	ft. 2		3	ft. 3-17-03
			WELL'S ST	ATIC WAT	IER LEVEL		5.92 ft.	below land	surface mea	sured on mo/da	ay/yr	
-	NW	- NE		Pump test	data: We	ell water	was		ft. after	hour	s pumping	gpm (c
9			Est. Yield		gpm: We	ell water	was		tt. after	hour	s pumping	gpm m
∰ W –	<u> </u>	E	Bore Hole D	FR TO BE	C.O	in.to เริยีบี	blic water s		ft. and 8 Air o	onditioning	11. to	ft.
			1 Dom	estic 3	Feed lot	6 Oil	field water	supply	- 9 Dew	hours onditioning atering	12 Other (S	Specify below)
	Sw	- SE	2 Irriga	ation 4	Industrial	7 La	wn and gard	den (domes	stic) 10 Mor	nitoring well)	
†										No X If ye		
	S		submitted							infected? Yes		
5 TYPE O	F BLANK CAS			5	Wrought li	ron		ete tile		G JOINTS: GIU	ued	Clamped
1 Ste		3 RMP (SR)	. 6	Asbestos-	Cement	9 Other	(specify be	low)		Ided	
(2 PV		4 ABS		7	Fiberglass	:				Th	readed	Flush
Blank casin	g diameter	2	in. to	12.5	ft., Dia		in. t	0	ft., Dia	ess or gauge N) Asbestos-cer	in. to	ft.
Casing heig	t above land	surface	Flush	in., w	eight	0	.703	lbs./f	t. Wall thickn	ess or gauge N	o. S	ch. 40
				:			Ę	PVC	10	Asbestos-cer	nent	
1 Ste		3 Stainle		5	Fiberglass Concrete t	i ile	8	RMP (SR) ABS	11	Other (specify None used (o	/) 	
2 Bra SCREEN O		4 Gaivar	nized steel GS ARE	0			9 d wrapped	ABS	8 Saw c	ut	11 None	(open hole)
	ntinuous slot		Mill slot						9 Drilled	holes		(0)000
2 Loi	uvered shutter	4	Key punched		7	Torch o	ut		10 Other	(specify)		
SCREEN-P	ERFORATED	INTERVALS:	From	12.5	ft. te	o 	22.5	ft.	From	ft	. to	ft.
			From		ft. to	•		^{ft.}	From	ft	. to	^{ft.} 🛪
GR	AVEL PACK I	NTERVALS:	From	10	ft. to	•	23	ft.	From	ft	. to	^{ft.}
			From		ft. te	0		ft.	From	ft	. to	ft.
GROUT	MATERIAL:	1 Neato	ement	2 Cem	erit grout	4	3 Ben	tonite	4 Other	Concrete	·	
		0			. ⊢rom		ft. t			rom 14 A		
	nearest sourc ptic tank	e of possible c	ontamination 4 Lateral li		7 -	Dit orbo			estock peris		bandoned w)il well/ Gas v	
	wer lines		5 Cess poo						tilizer storage		ther (specify	
	atertight sewer	lines	6 Seepage			eedyard	5		ecticide storag		(
Direction fro	-							How man	-			
FROM	TO	CODE		HOLOGIC	LOG		FROM	TO		PLUGGING	INTERVALS	
0	0.5		ncrete									0
0.5	5		i Clay, bla an Clay, ta									G
8	23		nd, browr		rained							
		Jai		<u>,</u>								
·												
	·											
			·····									
								5				
					This water	well was				(3) plugged und		
-	on (mo/day/yr)		3	-11-03						st of my knowle		ef. Kansas 4-9-03
	Contractor's L			53					Record was co	ompleted on m	o/day/yr)	4-9-03
under the bi	USINESS NAME	of C	Geotechn	ical Sel	vices, I	nc.	by (sig	nature)	tot of Health ar	d Environment,	A Wat	2005 W
Jackso	n St., Ste. 420.	Topeka, Kansas	s and circle the s 66612-1367.	Telephone	swers. sen e: 913-296-	5545. Se	nd one to WA	ATER WELL	OWNER and	retain one for you	ir records.	

GSI Job No. 2111034

ę

MW-7A

~ ~